

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY


Land Office State Pa

Lease No. 07000

Unit 25 of sec. 27 is

designated drilling unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

_____ 1951

Well No. _____ is located 300 ft. from $\left\{ \begin{matrix} N \\ S \end{matrix} \right\}$ line and 300 ft. from $\left\{ \begin{matrix} E \\ W \end{matrix} \right\}$ line of sec. 27

27 (1/4 Sec. and Sec. No.) 27 (Twp.) 11 (Range) R. M. P. M. (Meridian)

Ind. Leds Canyon (E&F) (Field) Ind. Leds (County or Subdivision) Ind. Leds (State or Territory)

The elevation of the derrick floor above sea level is 3340 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Added Note 1-7-51.

Drilled to 110' and set 100' of 10-3/8" casing. Cemented with 50 sacks of regular cement with 100# calcium chloride. Circulated cement. Tested pipe with 500# pressure for 30 minutes. Pipe o.k.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company British-American Oil Prod. Co.

Address Box 3107
Oklahoma City, Oklahoma

By Jeff Callahan
Jeff Callahan
Title Field Foreman