

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 070041
Unit Cleveland Federal

SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|--|--|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 17, 1961

Well No. 1 is located 1021 ft. from N line and 700 ft. from EX line of sec. 20

NW Section 20 21-N 9-W T.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Fulcherutz San Juan T.M.P.M.
(Field) (County or Subdivision) (State or Territory)


The elevation of the derrick floor above sea level is 5341 ft.

DETAILS OF WORK

State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is intended to Plug & Abandon this well in the following manner due to non commercial production:

1. Spot 50 sks. cement plug across open hole - 2175-2325.
2. Find free point & cut casing.
3. Spot 20 sks. cement plug across stub.
4. Pull 5 5/8" casing.
5. Spot 10 sks. cement plug in bottom of surface casing.
6. Spot 10 sks. cement plug in top of surface casing.
7. Set 4' x 4" pipe as permanent dry hole marker.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company
Address Box 900
Farmington, New Mexico
By _____
Title Petroleum Engineer