

20CC
2-F

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
XXXXXX Federal XXXXXX

5. State Oil & Gas Lease No.
SF-078092

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Beta Development Co. 3. Address of Operator 234 Petroleum Club Plaza, Farmington, N.M. 4. Location of Well UNIT LETTER C 790 FEET FROM THE North LINE AND 1850 FEET FROM THE West SECTION 27 TOWNSHIP 27 N RANGE 11 W NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 6370' GR 7. Unit Agreement Name 8. Farm or Lease Name Douthitt Federal 9. Well No. 1 10. Field and Pool, or Wildcat Basin Dakota 12. County San Juan
--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-24-66 Rigged up work-over unit.

3-25-66 Tbg. stuck on bottom, worked loose. Circ. approx. 4500' drlg. mud out of hole. Circ. out 94' sand & shale. CO to TD 6660'. Circ. 2 hrs on bottom to clean hole. POH. Ran corrosion log, found pipe bad @ 3300-4190'. Set Baker Model "D" producing packer @ 6525'. WIH w/tbg & Baker Model "D" locator assembly. Ran 205 jts 2 3/8" 8rd tbg w/22' pup jts on top of string w/3 jts 97' 1-1/4" integral tbg tail pipe; total 6613'. Pumped in 100 bbls oil mixed w/Ken-Pac behind tbg. Flushed tbg w/27 bbls oil. Landed tbg @ 6622' w/6000# on packer and 22,000# on donut.

3-26-66 Stripped cellar, rigged up BOP. Swabbed out light drlg mud, water with small amount of gas. Acidized tbg w/500 gals 15% reg mud acid, flushed w/27 bbls water; on vacuum in 5 minutes. Swabbed and kicked well off. Re-ran swab to keep well blowing. Gauaged 2060 MCF after 5 hrs w/1/2" stream water. Rig 7-AM March 27, 1966.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original signed by:
SIGNED **JOHN T. HAMPTON**

TITLE **Manager**

DATE **March 29, 1966**

Original Signed **Henry C. Arnold**
APPROVED BY

TITLE **Supervisor Dist. # 3**

DATE **MAR 30 1966**

CONDITIONS OF APPROVAL, IF ANY: