

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122
Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Sasia Sabota Formation Sabota County San Juan
Initial X Annual _____ Special _____ Date of Test 8-20-64
Company PAN AMERICAN PETROLEUM CORP. Lease H. B. McGrody "B" Well No. 1
Unit P Sec. 24 Twp. 27N Rge. 12W Purchaser _____
Casing 4-1/2 Wt. 10.5 I.D. 4.032 Set at 6322 Perf. 6223-28 To 6234-46
Tubing 2-3/8 Wt. 4.7 I.D. 1.995 Set at 6346 Perf. Open To Ended
Gas Pay: From 6223 To 6346 L 6243 xG .700 -GL 4372 Bar.Press. 12
Producing Thru: Casing _____ Tubing X Type Well Single
Date of Completion: 8-23-64 Packer None Reservoir Temp. _____
Single-Bradenhead-G. G. or G.O. Dual

OBSERVED DATA

Tested Through (None) (Choke) (None) Type Taps Flange

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Line) Size	(Choke) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI	7 day					1912		1930		
1.	1 inch	.750	361			361	60° est.	750	60° est.	3 hr.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w p_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3530		353	1.000	.9238	1.043	4213
2.							
3.							
4.							
5.							


PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 1942 P_c 3,771.364

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w /P _c
1.									
2.									
3.									
4.									
5.									

Absolute Potential: 4792 MCFPD; n .75
COMPANY PAN AMERICAN PETROLEUM CORPORATION
ADDRESS Box 488, Farmington, New Mexico
AGENT and TITLE F. L. Mahara, District Engineer
WITNESSED By: ORIGINAL SIGNED BY
COMPANY F. W. Foell

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressibility factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .