#### UNITED STATES

# DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

			, 5.	Lease Number
1 T	ype of Well	1890	6.	If Indian, All. o
	GAS		<del>)</del>	Tribe Name
2 N	ame of Operator	FEB 2000 RECEIVED	7.	Unit Agreement Na
-	BURLINGTON	OILCON, DIV		
2 7	ddress & Phone No. of Opera	200000000000000000000000000000000000000	8.	Well Name & Numbe Lodewick #5
	PO Box 4289, Farmington, M		٥	API Well No.
	PO BOX 4289, Farmington, N	4 8/499 (505) 326-9/00	9.	30-045-06331
4 T.	ocation of Well, Footage,	Sec T P M	10	Field and Pool
	90'FSL, 990'FWL, Sec.19, T		10.	Filcher Kutz PC
,	30 FBE, 330 FME, Sec.13, 1	-2/-N, R-3-N, NMEM	11	County and State
				San Juan Co, NM
		NDICATE NATURE OF NOTICE, REPORT	r, other	DATA
Т	ype of Submission	Type of Action	e ni	
	_X_ Notice of Intent	<del></del>	ge of Pla	
	Cubacanent Depart		Construc	
	Subsequent Report		r Shut o	Fracturing Ff
	Final Abandonment	Casing Repair water Altering Casing Conve		
		X_ Other - Restimulation		o injection
13.	Describe Proposed or Comp	pleted Operations		
	1. Pull 1" tubing.			
	2. Clean out (drill out)	from 2,410 - 2,590.		
		-,		
	3. Run OH log.			
	<b>9</b> '	new TD and cement to surface $w/\epsilon$	649.8 cu	. Ft. of cement.
	4. Run 2 7/8" casing to 1	new TD and cement to surface w/6 B/G" w/2% sodium metasilicate, !		
	4. Run 2 7/8" casing to 1 Lead: 295 sks Class "1		5 pps gi	lsonite,
	4. Run 2 7/8" casing to 1 Lead: 295 sks Class "1	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod:	5 pps gi	lsonite,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod:	5 pps gi ium meta	lsonite, silicate,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane.	5 pps gi ium meta	lsonite, silicate,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps 5. Selectively perforate	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic	5 pps gi ium meta	lsonite, silicate,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps 5. Selectively perforate 6. Clean out well.	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic	5 pps gi ium meta	lsonite, silicate,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps 5. Selectively perforate 6. Clean out well.	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic	5 pps gi ium meta	lsonite, silicate,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps 5. Selectively perforate 6. Clean out well.	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic	5 pps gi ium meta	lsonite, silicate,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps 5. Selectively perforate 6. Clean out well.	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic	5 pps gi ium meta	lsonite, silicate,
	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps 5. Selectively perforate 6. Clean out well. 7. Return well to product	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic	5 pps gi ium meta ctured C	lsonite, silicate,
14.	4. Run 2 7/8" casing to a Lead: 295 sks Class "I % pps cellophane. Tail 5 pps gilsonite, % pps 5. Selectively perforate 6. Clean out well. 7. Return well to product	B/G" w/2% sodium metasilicate, ! l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic	5 pps gi ium meta ctured C	lsonite, silicate,
. (	4. Run 2 7/8" casing to a Lead: 295 sks Class "I way pps cellophane. Tail 5 pps gilsonite, way pps 5. Selectively perforate 6. Clean out well.  7. Return well to product the product of the product that the product of	B/G" w/2% sodium metasilicate, ! 1: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Piction.  e foregoing is true and correct	5 pps gi ium meta ctured C	lsonite, silicate, liffs formation.
<b>14.</b> (Sign	4. Run 2 7/8" casing to a Lead: 295 sks Class "I way pps cellophane. Tail 5 pps gilsonite, way pps 5. Selectively perforate 6. Clean out well.  7. Return well to product the product of the product that the product of	B/G" w/2% sodium metasilicate, ! 1: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Piction.  e foregoing is true and correct  Title Regulatory Administra	5 pps gi ium meta ctured C	lsonite, silicate, liffs formation.
Sign	4. Run 2 7/8" casing to a Lead: 295 sks Class "I way pps cellophane. Tail 5 pps gilsonite, way pps 5. Selectively perforate 6. Clean out well.  7. Return well to product the product of the product that the product of	B/G" w/2% sodium metasilicate, !  l: 25 sks Class "B/G" w/ 1% sod: s cellophane. , acidize, and foam fracture Pic  tion.  e foregoing is true and correct  Title Regulatory Administration.	5 pps gi ium meta ctured C	lsonite, silicate, liffs formation.



# Lodewick #5

## Section 19 M, T-27 -N R-09 -W San Juan, New Mexico

### Kutz Canyon Pictured Cliffs Field Wellbore Schematic

