(Feb. 1951)				
				l

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	anta	£ 0
	1605	
Unit		

SUNDRY NOTICES AND REPORTS ON WELLS

SUNDRY NOTICES	
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO CHARGE TEMPORAL NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO TEST WATER SHOT-OF PERAIP WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	June 10, , 1960
Well No. 46 is located 1650 ft.	from $\left\{\begin{matrix} \mathbf{N} \\ \mathbf{S} \end{matrix}\right\}$ line and $\left\{\begin{matrix} 650 \\ \mathbf{W} \end{matrix}\right\}$ line of sec. $\left\{\begin{matrix} 23 \\ \mathbf{W} \end{matrix}\right\}$
E/4. /4 .ec.23 27.	(Meridian)
(½ Sec. and Sec. No.) (Twp.) Planco Pass Verde San	(Range) (Meridian) Juan Rev Kexico
(Field) (Co	onnty or Subdivision) (State or Territory)
	ea level is 5940 ft.
State names of and expected depths to objective sands; ship points, as concerning with 250 sacks of the concerning with 250 sacks of the concerning with section of the	ETAILS OF WORK how sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen all other important proposed work) 5° liner from 3700-4500.
(State names of and expected depths to objective sands; at ing points, as concerning with 250 sacks of Point Lookout section of Fig. and sand-water frac - 1500 Tunderstand that this plan of work must receive app. R & G DETALIES COMM.	ETAILS OF WORK how sizes, weights, and lengths of proposed casings; indicate mudding jobs, comen all other important proposed work) 5" liner from 3700-4500. 5 cement. perforate entire 288 Verde two shots per foot bbis water and 40,000 Sanglille GIL CON COM DIST. 3 Droval in writing by the Geological Survey before operations may be commenced. PANY, INC.
(State names of and expected depths to objective sands; at ing points, as operator intends to set 4.5 comenting with 259 sacks of Point Lookout section of Metallic sands water frac - 1500 Tunderstand that this plan of work must receive approximately a Company R & C DRIALDES COM	ETAILS OF WORK how sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) 5" liner from 3700-4500, 6 cement, perforate entire esa verde two shots per foot bbis water and 40,000 Sanfill CIL CON COM CIST. 3 proval in writing by the Geological Survey before operations may be commenced. PANY, INC.
(State names of and expected depths to objective sands; all ing points, and points are intended to set 4.5 concenting with 250 sacks of Point Lookout section of Me and soud-water free - 1500 Tunderstand that this plan of work must receive approximately	ETAILS OF WORK how sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement all other important proposed work) 5. liner from 3700-4500, 5. cement, perforate entire cas verde two shots per foot bbis water and 40,000 Santilly UL1 1980 CIL CON COM CIST. 3 proval in writing by the Geological Survey before operations may be commenced.