92/255

## STATE OF NEW MEXICO

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is net to be used for reporting packer leakage tests o Southeast May Maylor

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator	Mer	dian	Oil Inc	Lease!	tierfan	†c N	7ell 10. <u>89</u>	
						County \	anJuan	
weii: U	mt			TYPE OF PI	NOO.	METHOD OF PROD. (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Cog.)	
Upper	HAME OF RESERVOIR OR POOL		(Off or Ges)			71		
mpietion	MESAVERDE			602		Flour	1 1 63	
movetion DAKOTA				Gra		Flour	Tha	
			PRE-FLO	W SHUT-IN P	RESSURE DAT			
Hour, date shut-in Length of time shut		n Si press. psig		Stabilized? (Yes or No)				
Lower	Hour, date shut-in Length of time shut-in		SI press. paig		Stability Stability	ted? (Yes or No)		
mpletion	1-0	<u> </u>	7 1	JA45		575		
		· 1-	12.82	FLOW TEST		Alphon or Lowert Lou	()e>	
Deanemino TIM	et (hour, dete	LAPSED TIME	13-93 PRESSURE		PROD. ZONE		REMARKS	
hour.		SINCE#	Upper Completion	Lawer Completion	TEMP.			
:-11	- 33		5	843	<del> </del>	MESAVE	ERNE Lone	
1-16	2.93		5	843		is disc	onnected	
	3.93		5	843				
			-					
	197		5	-219				
	5- <sup>2</sup> 3		5	393				
roductio	on rate di	ring test						
Nil.		, BOI	PD based on	Bbls.	in Ho	ours Grav.	GOR	
/II								
Jas:					u (Orifice or M			
			MID-TE		SI press. paig	TA Stabl	Nzed? (Yes or No)	
Upper Completion	Hour, date s	<u></u> -	Langin or time and		Si press, perg	Stabi	Ilized? (Yes or No)	
Lower			Length of time shu	Length of time shut-in		Sie		
Completion	Ί					MEGE		
			•			FEB I	19 <b>93</b>	
						01 000	I There .	

(Continue on reverse side)

CIL CON. DIV.

FLOW TEST NO. 2 Zone preducing (Upper or Lower): Commenced at (hour, date) \*\* PRESSURE PROD. ZONE LAPSED TIME DEMARKS TEMP. hour, detail SINCE P. **Upper Completion** Lower Completion Production rate during test BOPD based on \_\_\_\_\_\_ Bbls. in \_\_\_\_\_ Hours. \_\_\_\_ Grav. \_\_\_\_ GOR \_\_\_\_\_ MCFPD: Tested thru (Orifice or Meter): Remarks: \_

hereby certify that the information herein contains	d is true and	d complete to the	best of my knowledge.
---	---------------	-------------------	-----------------------

Approved FEB 1 1993	19Operator Me	ridian Oil The		
New Mexico Oil Conservation Division	Ву	SUSAN DOLAN OPERATIONS ASSISTANT		
Original Signed by CHARLES GHOLSO	<del>-</del> / <del></del>			
DEPUTY OIL & GAS INSPECTOR DIST		१८७ में हैं अ <b>ट</b> ड		

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packet leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packet of the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator snail notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are mutton for pressure stabilization. Both zones shall remain shuton until the well-head pressure in each has stabilized, provided however, that they need not remain shuton more than seven days.
- 1. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for ieven dass in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- A. Fire Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fafteen-manute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway pount) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Axtec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).