

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
AMOCO PRODUCTION COMPANY

Attention:  
Pat Archuleta

3. Address and Telephone No.  
P.O. BOX 800 DENVER, COLORADO 80201

303-830-5217

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1600' FSL 940' FWL Sec. 21 T 27N R 10W UNIT L

5. Lease Designation and Serial No.

SF-077386-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

E. J. Johnson C #1

9. API Well No.

3004506361

10. Field and Pool, or Exploratory Area

Gallup

11. County or Parish, State

SAN JUAN NEW MEXICO

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give markers and zones pertinent to this work.)

subsurface locations and measured and true vertical depths for all

MIRUSU 12/18/97.

Set CIBP at 5550', load and test csg to 500#. Held okay.

Spot cement plug inside csg from the top of CIBP at 5550' to 5350' w/16 sxs CI-B cement.

Spot cement plug inside csg from 3616' to 3400' w/16 sxs CI-b cement.

" " " " " 2960 - 2760 " " "

Spot cement plug inside csg from 2059' to 1540' w/32 sxs CI-B cement.

Shoot sqz holes at 1140', and sqz perf, would not circ only take 1/2 bbls, TIH set cement ret at 900', prep to sqz, sting into ret pump 38 sxs CI-B cement below ret, sting out and spot 17 sxs CI-B inside csg to 687'.

Sqz perfs at 410' w/153 sxs CI-B cement, circ to surface, cut off wellhead, top off csg strings to surface, install marker.

RDMOSU 12/23/97.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Staff Assistant

Date

01-14-1998

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

/S/ Duane W. Spencer

JAN 21 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instructions on Reverse Side

AMOCO