## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

B	udget	Bureau	No.	42-R358.4.
F	orm A	pproved		

Land Office Fermington

Losso No. SP-078356
Huerfanito

NOTICE OF INTER NOTICE OF INTER NOTICE OF INTER NOTICE OF INTER	NTION TO DRILL  NTION TO CHANGE PL  NTION TO TEST WATER  NTION TO RE-DRILL O  NTION TO SHOOT OR AL	ANSR SHUT-OFFPR REPAIR WELL	s	SUBSEQUENT REPO	ORT OF WATER	SHUT-OFF		XX	1
NOTICE OF INTER NOTICE OF INTER NOTICE OF INTER	NTION TO TEST WATER NTION TO RE-DRILL OF NTION TO SHOOT OR A NTION TO PULL OR AL	R SHUT-OFF OR REPAIR WELL ACIDIZE	3	SUBSEQUENT REPO	DE OF CHOSE	O. F		-	
NOTICE OF INTEN	NTION TO RE-DRILL O NTION TO SHOOT OR A NTION TO PULL OR AL	R REPAIR WELL	S		OUT OF SHOOT	ING OR ACIDIZMIC	_	1	
NOTICE OF INTEN	NTION TO SHOOT OR A	ACIDI7F	-	ODSEGRENT KEND	ORT OF ALTER	NG CASING		7	r -
NOTICE OF INTEN	NTION TO PULL OR AL		S	UBSEQUENT REPO	RT OF RE-DRI	LLING OR REPAIR			15
NOTICE OF INTEN		TER CASING	SI	UBSEQUENT REPO	RT OF ABAND	ONMENT			1
	NTION TO ABANDON WI	ELL		UPPLEMENTARY W	VELL HISTORY.		<u>'</u>	1	133
						!!			_
	(INDICATE	ABOVE BY CHECK N	MARK NATURE	OF REPORT, NOT	CE OR OTHER			110	gar <sub>15</sub>
					-L, OK OTHER	DATA)			
QI	kelly-Govt.					May 22	1.0	. 63	ł.
D N.T	verrh-CoAf		<b></b>				, 15	)	
ell No	is located	2050 ft. fr	om N	line and 10	00 tt t	<b>100</b> 0	_	_	
winu+	22		X(K)X		== 1t. IIO	$\mathbf{W}$ line of	sec	3	
(½ Sec. and	22 Sec. No.)	27 N.	9 V	V. N	MPM				
		San J	(Range)	Ċ	Meridian)				
(Field	1)	(Coun	ity or Subdivis	ion)		New Mexic	20		
a alazzati	ungrade				,	could of lefficity)			
ment first wrns while	xpected depths to objects 4-1/2 Of stage w/100	DETA  Coctive sands; show.  ing points, and al  D 10.5# JS:  D ax 8% gel	AILS OF sizes, weights il other impor  5 8 rd 83	WORK s, and lengths of print proposed we TAC casis	proposed casin ork) Mg (6920) PD 3:30	.50'). Set ( PM 5-21-6)	ng jobs, cem ng 693(	0°. Ociz	nud
ment first wrns while menting. M, 5-21.	xpected depths to obje	DETA  cetive sands; show ing points, and all  D 10.5# J5:  D ax 8% gel  Max. cm  2-stage too	level is 6 AILS OF sizes, weights Il other impor 5 8 rd 8 1, 100 s	WORK  and lengths of print proposed we  TAC casis  Neat. Page 1406	proposed casin ork) og (6920, PD 3:30	,50'), Set ( PM 5-21-6) (proceted of	e jobs, cem at 691 Goo	0'. Od z whil	
ment first urns while menting. M, 5-21. cer tool w/	stage w/10; stage w/10; comenting. Open Baker; Good mud r/2200# and s	DETA  cetive sands; show: ing points, and al  D 10.5# JS: 0 sx 8% gel  Max. cm 2-stage toe returns whilet slips.	level is 6 AILS OF sizes, weights If other impor 5 8 rd 85 1, 100 s 1, press of at 236 lie come	WORK  and lengths of print proposed we  TAC Casin  X Neat. Faure: 1406  5. Cementing. Me	oroposed casin ork) og (6920 PD 3:30 F. Rec ented w/ ax. omt	50'). Set (PM 5-21-6) (proceed of 75 sx 8% g). Pressure:	t 691 Goodsing val. PD 500#.	0'. Od z whil	
ment first urns while menting. M. 5-21. cer tool w.	stage w/100 cementing. Open Baker (	DETA  cetive sands; show: ing points, and al  D 10.5# JS: 0 sx 8% gel  Max. cm 2-stage toe returns whilet slips.	level is 6 AILS OF sizes, weights If other impor 5 8 rd 85 1, 100 s 1, press of at 236 lie come	WORK  and lengths of print proposed we  TAC Casin  X Neat. Faure: 1406  5. Cementing. Me	oroposed casin ork) og (6920 PD 3:30 F. Rec ented w/ ax. omt	50'). Set (PM 5-21-6) (proceed of 75 sx 8% g). Pressure:	t 691 Goodsing val. PD 500#.	0'. Od z whil	
ment first urns while menting. M, 5-21. cer tool w/	stage w/100 stage w/100 comenting. Open Baker in Good mud in 12200# and stage w/2200# and stage w/220#	DETA  cetive sands; show: ing points, and al  D 10.5# JS: 0 sx 8% gel  Max. cm 2-stage toe returns whilet slips.	level is 6 AILS OF sizes, weights If other impor 5 8 rd 85 1, 100 s 1, press of at 236 lie come	WORK  and lengths of print proposed we  TAC Casin  X Neat. Faure: 1406  5. Cementing. Me	oroposed casin ork) og (6920 PD 3:30 F. Rec ented w/ ax. omt	50'). Set (PM 5-21-6) (proceed of 75 sx 8% g). Pressure:	t 691 Goodsing val. PD 500#.	0'. Od z whil	
ement first turns while menting. PM, 5-21.	stage w/100 cementing. Open Baker (	DETA  cetive sands; show ing points, and all  D 10.5# J5:  D ax 8% gel  Max. cm  2-stage too	level is 6 AILS OF sizes, weights Il other impor 5 8 rd 8 1, 100 s	WORK  and lengths of print proposed we  TAC casis  Neat. Page 1406	oroposed casin ig (6920 PD 3:30 if. Rec. inted w/ ax. omt	SO'). Set PM 5-21-63 iproceted of 75 sx 8% greesure:	e jobs, cem at 691 Goo	0°. Odi	1

New Mexico Oil & Gas Conservation Commission, Antec (1 copy)
El Paso Matural Gas, El Paso, Texas (1 copy)
El Paso Matural Gas, Farmington (1 copy)

U. S. Geological Survey, Farmington (5 copies) (Commissioner of Public Lands, Sants Fe (1 copy)