

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other Instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R-424.

LEASE DESIGNATION AND SERIAL NO.

SFC 78089

IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Gulf Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State or Federal requirements. See also space 17 below.)
At surface

1600' FNL & 1600' FWL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Scott "E" Federal

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

W. Kutz Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 23-T27N-R11W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6297' DF

12. COUNTY OR PARISH

San Juan

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting; any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

POH with production equipment. Set CIBP at 1925'. Circulate hole with abandonment mud. Cap CIBP with 25 sacks Class "B" neat cement. GIH with 2-3/8" tubing open-ended to 1450'. Spot 75 sacks Class "B" neat cement plug 1450'-1275'. Spot 50 sacks Class "B" neat cement plug 920'-820'. Spot 50 sacks Class "B" neat cement plug 140'-90'. Spot 25 sacks Class "B" neat cement surface plug. Install dry hole marker; clear and clean location.

See attached modifications

APPROVED

APR 30 1981

James F. Sims
JAMES F. SIMS

18. I hereby certify that the foregoing is true and correct

DISTRICT OIL & GAS SUPERVISOR

SIGNED R. D. Pite

TITLE Area Engineer

DATE 4-16-81

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

U. S. GEOLOGICAL SURVEY
P. O. Box 959
Farmington, New Mexico 87401

4-30-81

Re: Permanent Abandonment

Well: #4 Scott "E" Federal

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached conditions and terms for Permanent Abandonment of Wells on Federal Lands.
2. The Farmington office (telephone (505) 325-4472) is to be notified with sufficient time for a representative to witness all plugging operations.
3. Blowout prevention equipment is required.
4. In addition to normal filling of pits and cleanup of location, additional surface restoration work may be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Bureau of Land Management for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
5. The surface management agency is to be notified when surface rehabilitation is complete.
6. The following modifications to your plugging program are to be made (when applicable):
 - a) Perforate 5½" casing at 1345' and place cement plug inside + outside casing to 1245'.
 - b) Perforate 5½" casing at 920' and place cement plug inside + outside casing to 820'.
 - c) Perforate 5½" casing at 165' and place cement plug inside + outside casing to surface.

Office Hours: 8:00 A.M. to 5:00 P.M.
Farmington Personnel to be notified:

Home Telephones:

Ray Swanson: Petroleum Engineering Technician - 325-8189
Fred Edwards: Petroleum Engineering Technician - 325-7885
Ken Baker: Petroleum Engineering Technician - 327-2170