

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
LEASE DESIGNATION AND SERIAL NO.

SF 078089

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Gulf Oil Corporation		8. FARM OR LEASE NAME Scott "E" Federal	
3. ADDRESS OF OPERATOR P. O. Box 670, Hobbs, NM 88240		9. WELL NO. 4	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1600' FNL & ¹⁰⁴⁰ 1600 ' FWL		10. FIELD AND POOL, OR WILDCAT W. Kutz Pictured Cliffs	
14. PERMIT NO.		11. SEC. T. R. M. OR RLC AND SURVEY OR AREA sec. 23 - 27N-11W	
15. ELEVATIONS (Show whether BP, RT, CR, etc.) 6297' DF		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Re-completion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

POH with tubing. Set CIBP at 1910'. Displace hole with abandonment mud. Spot 25 sack plug on CIBP, test casing 500#. Cut casing at 1049'; cannot POH. Set cement retainer at 1233', pump 50 sacks Class "B". Plug 1233'-1345' inside and outside casing. Cut casing 900' and POH. GIH with tubing to 950', spot 75 sack plug 950'-820'. Spot plug 165' - surface. Set dry hole marker. Clean and clear location. P&A 8-1-82.

RECEIVED
OCT 22 1984
OIL CON. DIV.
DIST. 3

APPROVED

OCT 18 1984

M. MILLENBACH
AREA MANAGER

18. I hereby certify that the foregoing is true and correct

SIGNED

R. D. Pitre

TITLE

Area Engineer

DATE

8-17-82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side