



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 078421  
Unit NW 1/4 Sec 20

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 28, 1953

Well No. 1 is located 1750 ft. from N line and 990 ft. from XX line of sec. 20

SW SW NW (1/4 Sec. and Sec. No.) 27N 9W (Twp.) (Range) N M P M (Meridian)  
Fulcher Kutz (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6369 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

30

Well was spudded on January with cable tools and drilled to 92' below ground level where 8 5/8 casing was cemented with 85 sacks regular cement and circulated on February 11. Rotary tools were then moved on and surface casing tested with 500 lbs. for thirty minutes with no leaks resulting. Plug was drilled and cement tested in same manner. Hole was carried to 2242 where 5 1/2 casing was set with 100 sacks regular cement. cable tools were then moved on and hole carried to 2390. Hole was shot with 225 quarts 5 N G from 2242 to 2333, cleaned out and one inch tubing set to 2320. 2233

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Denman Oil & Drilling Corp.Address Box 306Farmington, N MBy R. L. YoungTitle Vice Pres

1944

1944

1944

1944

1944

1944

1944

1944

1944

1944