Form 9-331 (May 1963)

## UNITED STATES DEPARTMENT OF THE INTERIOR (Other instructions on re-

SUBMIT IN TRIPLICATE\*

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY		NM-035634	
	OTICES AND REPORTS ON WELLS proposals to drill or to deepen or plug back to a different reservoir. PLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME
1.		7. UNIT AGREEMENT NA	ME
WELL GAS WELL OTH	ER		_
2. NAME OF OPERATOR		8. FARM OR LEASE NAME	
PAN AMERICAN PETRO	LEUM CORPORATION	H. B. McGrady "A"	
3. ADDRESS OF OPERATOR		9. WELL NO.	
P. O. Box 480, Farmington, New Mexico  4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface  1115 FWL and 1545 FNL		2 10. FIELD AND POOL, OR WILDCAT  Basin Dakota  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SW/4. NW/4. Section 23, T-27-N, R-12-W	
	5937 (RDB)	San Juan	New Mexico
	Appropriate Box To Indicate Nature of Notice, Report, of Intention to:	or Other Data	

REPAIRING WELL PULL OR ALTER CASING WATER SHUT-OFF

TEST WATER SHUT-OFF MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING FRACTURE TREAT SHOOTING OR ACIDIZING ABANDON MENT\* ABANDON\* SHOOT OR ACIDIZE Well History CHANGE PLANS REPAIR WELL (Note: Report results of multiple completion on Weil Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

The above well was spudded on 7-19-64 and drilled to a depth of 357'. 8-5/8" casing was set at that depth with 230 sacks cement containing 2% calcium chloride. Cement circulated to surface. After waiting on cement tested casing with 900 psi. Test OK. Reduced hole size to 7-7/8" and resumed drilling.

Well was drilled to a depth of 6170'. 4-1/2" casing was landed at that depth with stage collar at 4325. Comerted first stage with 400 sacks coment containing 6% gel, 2 pounds medium Tuf Plug per sack and followed by 100 sacks neat cement. Cemented second stage with 1000 sacks cement containing 6% gel and 2 pounds Tuf Plug per sack. Cement circulated to surface. After waiting on coment tested casing with 3500 psi. Test OK.

Perforated 6067-73 with 3 shots per foot, 6094-6102 with 2 shots per foot, 6115-19 with 4 shots per foot. Fracked these perforations with 53,000 gallons water containing 1% calcium chloride and 5 pounds J-133 per 1000 gallons and 50,000 pounds sand. Dropped 30 ball sealers after 25,000 pounds sand in formation. Had 50 psi pressure increase when balls hit perforations. Breakdown pressure 3500 psi, average treating 3200 psi, average injection rate 39 BPM. Bridge plug set at 6050 and tested with 3500 pmi. Test OK. Perforated 6016-34 with 4 shots per foot. Fracked these perforations with 22,000 gallons water treated as above and containing 20,000 pounds sand. Breakdown pressure 2400 psi, average treating 3200 psi, average injection rate 39 BPM. Drilled out bridge plug and cleaned up well.

2-3/8" tubing landed at 6033 and well completed 8-18-64 as Basin Dakota Field Development Well. Preliminary Test 2750 MCFD.

18. I hereby certify that the foregating is true and correct	Fred L. Nabors, District Engineer			
SIGNED SIGNED BY	TITLE	- Chillip	DATE August	24, 1964
(This space for Federal or State office use)		AMILIA /	THE SECOND SECON	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE		ĎATE	<u></u>
		on Reverse Side	春日等 · #	]
*S	ee Instructions	on Reverse Side		

## Instructions

General: This form is designed for submitting proposats to perform certain well operations, and reports of such operations when completed, as indicated, on Peels and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions. Hem 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963 OF-685229

867-851