(Feb. 1951)						
ı						
						

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Suntu Fe						
Lease No.	N. Mex. 020498	j				
Unit	∛ockey					

	-W. Ter -FF-te
(INDICATE ABOVE BY CHECK MARK	k nature of report, notice, or other data) $\mathbf{J}_{\perp}\mathbf{n}\mathbf{u}_{\perp}\mathbf{r}\mathbf{y} = \mathbf{J}_{\parallel}\mathbf{p}_{\parallel}\mathbf{r}$
Vell No. 20 1450 ft. from N. W. 20 27N (Twp.) W. Kutz C. S. n. Ju. n. (County	m. ${N \brace S}$ line and 1450 ft. from ${E \cr W}$ line of sec

The elevation of the derrick floor above sea level is 6203 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1940 ft. Total Depth. 1831 Carring point. Hole fluged back to 1864. Water Frac open hole 1831 to 1864 with 850 obls. water, 25,000 lbs. sand. Breakdown pressure 1500 lbs. average treating pressure 950 lbs. Injection rate 37.5 3.P.M. Flush 2500 gal.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.				
Company Frank Yockey				
AddressBox_2055				
F.rmington, N.M.	By			
	Title Owner GPO 918507			