



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa FeLease No. 076421

Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<b>XXXX</b>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 10, 1960, 19

Turner-McAdams

Well No. 2-20 is located 950 ft. from [N] line and 490 ft. from [W] line of sec. 20T<sub>4</sub>/4 Section 20

(1/4 Sec. and Sec. No.)

T 27-N

(Twp.)

R 9-W

(Range)

N.M.P.M.

(Meridian)

Angel's Peak Dakota Ext.

San Juan County

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6,393 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate clogging, cobbles, cementing points, and all other important proposed work)

July 13, 1960. Tested 8-5/8" casing to 800' for 30 minutes prior to drilling out. No decrease in pressure. On 8/3/60 - after drilling to 6963' ran 2 1/2 joints 5-1/2" OD 15.5 J-55 casing with stage collar 2416'. 6966' overall, set at 6963'. Cemented first stage with 375 sacks 50/50 Pozmix, 4% gel, 12% Gilsomite per sack followed with 50 sacks neat cement. Good circulation throughout. On 8/4/60 at 1:30 AM cemented second stage with 100 sacks 50/50 Pozmix, 2% gel. Moved rotary off.

On 8/21/60 Switt Drilling Co. rigged up. Drilled out stage collar at 2416'. On 8/22/60 cleaned out to PBTD 6925' with 4-3/4" bit. Pressure tested casing with water to 3500 psi for 10 minutes with no pressure drop. Ran gamma ray correlation log. Found PBTD 6929' on electric log measurements. Perforated 6897-6904' with 4 jet shots per foot. Ran Baker Retrievalomatic packer on 2" tubing set at 6822'. See next page for further perforations and sand fracturing.

(Indicate that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.)

Company J. Glenn Turner & William G. SmithAddress Box 726Farmington, New Mexico.

By

C. Beeson Neal, Agent in Farmington  
Title \_\_\_\_\_

1897-674

6726-77  
6752-38

14/2/57-6504,

0 6712 6712

~~0 6730 6730~~

-----

1/2/57

1/2/57

