

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990'N, 990'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON* ☐
- (other) ☐

SUBSEQUENT REPORT OF

SEP 21 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
NM 02861

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Lodewick

9. WELL NO.
#3

10. FIELD OR WILDCAT NAME
Fulcher Kutz (PC)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 19, T-27-N, R-9-W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6524' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Attempt to circulate well with mud and spot a 50 sk plug.
- 2) Circulate well and tag plug at 2278'.
- 3) Spot a plug from 2278' to 2060'.
- 4) Perforate the 5½ casing at 1440 and squeeze a plug to 1340 behind the 5½" casing. Spot a plug from 1440 to 1327 inside the 5½" casing.
- 5) Perforate the casing at 201 and circulate cement down the 5½" casing and back to surface through the 5½ - 8 5/8 annular space.
- 6) Cut off the wellhead and install a dry hole marker.

RECEIVED

AUG 01 1984

OIL CON. DIV.

DIST. 3

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. D. Welch TITLE Production Engineer DATE SEP 17, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

JUL 30 1984

M. MILLENBACH
AREA MANAGER

NMOCC

*See Instructions on Reverse Side