Form 9-331a (Feb. 1951)						

(SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land	Offic	•			
Lease	No.	S.F.	0779	70 <b>-</b> B	

√EB 2 ₀ 1959

SUNDRY	NOTICES AI	ND REPORTS ON WELL	.S	
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	1747	
NOTICE OF INTENTION TO CHANGE P	LANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZIN	G	
NOTICE OF INTENTION TO TEST WAT	ER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING		
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	R	
		SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY	- I	
NOTICE OF INTENTION TO ABANDON	WELL			
(INDICA	TE ABOVE BY CHECK MARK N	NATURE OF REPORT, NOTICE, OR OTHER DATA)		
		Feb. 23,	, 19. <b>.59</b>	
NW NW sec. 19		line and 1166 ft. from W line  13 W NP  (Meridian)	7 19 19 19 19 19 19 19 19 19 19 19 19 19	
V-			FROM	
Undesignated (Field)	San Juan (County or	Subdivision) New Mexico Subdivision) (State d Tegrito	<del>50 - 6 19</del> 59	
• •		OIL	CON. CON.	
The elevation of the derrick	; floor above sea leve	el is 6121 ft. (kb)	DIST. 3	
	DETAII	LS OF WORK		
(State names of and expected depths t	o objective sands: show sizes	s, weights, and lengths of proposed casings; indicate n her important proposed work)	nudding jobs, cement-	
Feb. 7, 1959 Feb. 9, 1959	Spudded at 11: Ran 14 jts., 4 @ 407' (KB) with Plug down at 3	221, 32.30#, H-40, 9-5/8" casi th 200 saxs regular cement, k	ng and cemented gel, 3% CaCl <sub>2</sub> .	
Feb. 21, 1959 T.D. 5340'. Ran 185 jts., 5332', of new C. F. & I, 52 J-55, 15.5#, ss, S.T. & C. API casing and cemented at (KB) with 200 saxs 50/50 pozmix - regular cement mix, gel. Plug down at 3:30 a.m.				
Company Utah Souther	k must receive approval in v rn 011 Company National Bank Bl	writing by the Geological Survey before operations ma	ay be commenced.	
Denver, Colorado		n.	<i>:</i>	
		Ву		
		Title Production Supe	rintendent	