

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Re-entry of F&A Wildcat		5. LEASE DESIGNATION AND SERIAL NO. Tribal #14-20-0003-007
2. NAME OF OPERATOR Amstar Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo
3. ADDRESS OF OPERATOR Box 1400, Durango, Colorado		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface NW 1/4 NW 1/4, Sec. 20, T. 37N, R. 17W., San Juan County, New Mexico		8. FARM OR LEASE NAME Navajo Trust #4
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR Sec. 20, T. 37N, R. 17W South Table Mesa Area
		12. COUNTY OR PARISH San Juan
		13. STATE New Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING **Set 4-1/2" OD Csg.**

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/20/68 - Started drilling cement in top of 9-1/8" OD Csg., with 8-1/8" bit at 1:00 AM.

2/20/68 - Drilled and cleaned out hole with 8-1/8" bit to top of 7" OD Csg. stub at 3705'. Reduced bit size to 6-1/4" and drilled cement plug and cleaned out hole to 7095', original TD.

3/1/68 - Ran 50 jts. 4-1/2" OD 11.000 Csg. & 134 jts. 4-1/2" OD 12.250 Csg., set @ 7002' W/Larkin Guide shoe on bot., Larkin float collar at 7035' & (A) Cement liners @ 7700', 7565', 7400' & 7000'. Sandstones from 7000' to 7740', 7500' to 7544', 7130' to 7444', 7114' to 7070'. Halliburton cemented 4-1/2" OD Csg. W/215 cu. 20-30 Pounds, 21 Gal and 12-1/20 shoe gaskets per depth. Pumped 20 mins. of brine ahead of cement. Pumped plug to 7036' W/20000 pounds. rotated csg. while cementing. W.O.C.

3/2/68 - Ran 2 & 2 temp. survey, top of cement outside of 4-1/2" OD Csg. @ 3700'. Tested 4-1/2" OD Csg. W/20000 press. Hold ok.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE


Field Clerk

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:



RECEIVED

MAR 7 1968

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
FARMING

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either as shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon wells and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depth (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final reconnection for approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-485229

897-851