

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
Tribal #14-20-0603-927

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo Tract #4

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND

**Sec. 20, T-27N., R-17W.,
South Table Mesa Area**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH

San Juan

13. STATE

New Mex.

16. Appropriate Box To Indicate Nature of Notice, Report, or Other Data

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACID ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☒ ABANDONMENT* ☐
(Other) **Set cement retainer** ☒

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

3/4/68 - Swabbed 6.16 bbls. water with scum of heavy dead oil. Very light show of gas last 6 hrs. Pulled 2-3/8" Tbg., Baker Retrievo-matic Packer & seating nipple. Trip in-hole with 2-3/8" Tbg., Baker Model K Cement Retainer set at 7683'. Squeezed perfs. in 4-1/2" OD Cag. from 7736' to 7798' with 50 sz. class A cement, max. press. 23000, final press. 23000. Left 10 sz. cement in 4-1/2" OD Cag. from 7683 to 7798'. Trip out with 2-3/8" Tbg. & Baker setting tool. Perf. 4-1/2" OD Cag. from 7334' to 7500' with (1) Hyper Jet shot per ft. Ram 2-3/8" Tbg., Baker 2-3/8" x 4-1/2" Retrievo-matic Packer with seating nipple on top. Tbg. set at 7573' and packer at 7478'. Acidized 4-1/2" OD Cag. perfs. from 7334' to 7500' with 300 gals. HCl acid, max. press. 30000 avg. press. 20000, inj. rate 3/4 bbl. per min. Press. dropped to 10000 in 10 min. after shut down. Flowed back 13 bbls. load water.

3/5/68 - Swabbed & flowed 35 bbls. of acid water & residues. Swabbed 16.98 bbls. oil & 9.66 bbls. of water in 20 hrs. Made 32 trips fluid level from surface to 6000', max. swab depth 7300'. Gravity of oil 45.5, gas vol. to small to measure.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Field Clerk

DATE

3-4-68

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
MAR 3 1968
U. S. GEOLOGICAL SURV
FARMING

Instructions

General: This form is designed for submitting proposals to abandon certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or may be obtained from the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depth (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of placing of any casing, liner, or tubing placed and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-485229
807-811

