



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Navajo Allotted _____
Allottee L-149-Ind. 8466
Lease No. John Charles

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Report of perforation</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

John Charles
Well No. 7 is located 790 ft. from XX line and 1890 ft. from W line of sec. 13
SW/4 Sec 13 27N 9W 1890
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated - Dakota San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6017 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated 7" CD casing with 4 Lane Wells type "E" gun bullets per foot as follows:
6450'-6456', 6464'-6480'.
Sand fraced perforations 6450'-6456' and 6464'-6480'. Pumped down tubing, 20,000# of 40/60 sand and 27,105 gallons of crude oil. Flushed with 12,116 gallons crude oil. Used 1100# of admite, mixed 1/20# per gallon oil. HEP 4000# - 2800#. Max press. 4200#. Min. pressure 3600#. Injection rate 8.2 BPM.

Set Guiberson "BF" bridge plug on Lane Wells wire line at 6428'
Perforated 7" CD casing with 4 Lane Wells type "E" gun bullets per foot as follows:
6374' - 6390'

Sand fraced perforations 6374' - 6390'. Pumped down tubing, 20,000# of 40/60 sand and 26,100 gals of crude oil. Flushed w/1900 gals. of crude oil. Used 1250# of admite, mixed 1/20# per gal. oil. HEP 3700#. Maximum press 4400#. Min. press 3600#

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. inj. 8 BPM

Company Shelly Oil Company

Address Dr. 510

Farmington, New Mexico

By (Signed) P. E. Gosper

Title District Superintendent