

(SUBMIT IN TRIPLICATE)
**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

Land Office New Mexico
Lease No. 03300
Unit Florence

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS: 5 1959

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Water Frac.</u>	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 3, 1959

Well No. 15-D is located 1035 ft. from S line and 1135 ft. from E line of sec. 17


SE Sec. 17 27N 3W N.M.P.M.
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
South Blanco P. C. San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6749 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7-19-59 C.O.T.D. 2904'. Re-water fractured Pictured Cliffs perf. int. 2840-48;
2868-60; 2886-2900 (2 DJ/ft.) w/31,000 gallons 1% Calcium Chloride water,
and 35,000% sand. BD pr. none, max. pr. 2600%, avg. tr. pr. 1800%. I.R. 37 B.M.
Flush 2940 gallons. Spotted 250 gallons BDA on perforations. Dropped 2 sets
of 32 balls each and 2 sets of 10 each for 5 stages.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

El Paso Natural Gas Company

Company Box 997

Address Farmington, New Mexico

By ORIGINAL SIGNED B.H. MEANS

Title Petroleum Engineer