

(SUBMIT IN TRIPLICATE)

Land Office Santa FeLease No. H. H. 01800Unit Gentle #3

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Perforation</u>
	<u>Sand free</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Gentle #3July 6, 1956Well No. 1 is located 990 ft. from S line and 1290 ft. from W line of sec. 15SW/4 Section 15
(1/4 Sec. and Sec. No.)27N
(Twp.)9E
(Range)1. 2. 3. 4.
(Meridian)Gentle: Blanco
(Field)Santa Juan
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 6255 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated 5-1/2" O.D. casing 2215' - 2230' with 4 shots per foot for total of 240.

Sand-fraced through perforation 2215' - 2230' with 37,000# sand - with 2,520 gals. water to fill, 33,600 gals. water treating, 5,040 gals. water flush. Breakdown pressure 1700# - Max. 1200# - Min. 1200#. Injection rate 44 BPM. Treating time 12 min.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SEELY OIL COMPANYAddress Box 426Farmington, New Mexico

By

P. E. CooperTitle District Foreman

