

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

6. Lease Designation and Serial No.

SF-077974

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Lodewick

#2

9. API Well No.

3004506537 06464

10. Field and Pool, or Exploratory Area

Flucher Kutz PC

11. County or Parish, State

San Juan

New Mexico

1. Type of Well

☐ Oil Well

☒ Gas Well

☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

Pat Archuleta

3. Address and Telephone No.

P.O. BOX 800 DENVER, COLORADO 80201

303-830-5217

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

895' FSL

895' FWL

Sec. 18 T 27N R 9W

UNIT M

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRUSU 2/7/97.

Set CIBP at 2436', test csg to 500#. Held okay.

Shoot squeeze holes at 1566', could not pump into perfs at 1000#. Shoot squeeze holes at 157', was able to circ out perfs to surface w/ water.

Spot cmt plug inside csg from 2436'-1928', w/21 sks CI-B cement.

Spot cmt plug inside csg from 1928'-1403', w/21 sks CI-B cement.

Pump dn csg to perfs at 153' circ cmt to surface on the 3.5" and 5.5" w/86 sks CL-B cement.

Cut off wellhead and top off csg to surface, install marker.

RDMOSU 2/10/97

14. I hereby certify that the foregoing is true and correct.

Signed

Pat Archuleta

Title

Staff Assistant

Date

02-25-1997

(This space for Federal or State office use)

Approved by

[Signature]

Title

Date

MAR 6 1997

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

NMOC