

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____
Allottee John Charles
Allottee I-149-In. 0466
Lease No. John Charles

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<u>redaction</u>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Report of perforation</u>	
	<u>Report of sand-fracing</u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 3 is located 1500 ft. from S line and 1750 ft. from W line of sec. 13
Section 13 (1/4 Sec. and Sec. No.) 27E (Twp.) 9E (Range) Meridian (Meridian)
South - P.C. (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 5-1/2" casing (52 jnts. 2106') at 2112' with 150 sks. reg. cement.

Perforated 5-1/2" casing from 2010' to 2074' with 4 (9/16) chamberger bullets per foot for total of 256 shots.

Fractured through perforations from 2010' to 2074' with 40,000 gal. of sand and 37,800 gal. of water. Flashed with 3,780 gal. of water. Breakdown pressure 1100# - Max. 1150# - Min. 1100#. Time of treatment 19 min. Injection rate 68.3 BPM. Shut in 5 hrs.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Skelly Oil Company

Address on 426

Hardington, New Mexico

By _____

Title District Foreman