

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

I-149.8466

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

John Charles

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

SO. Blanco Pictured C

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

K-SEC.13-27N-9W

12. COUNTY OR PARISH

San Jaun

13. STATE

NM

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

TEXACO INC. (505) 325-4397

3. ADDRESS OF OPERATOR

3300 N. Butler, Farmington NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

1500' FSL and 1750' FWL of SEC.13

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6002' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TEXACO INC. has plugged and abandon the subject well. The following is a summary of the plugging.

RU. Dowell Spotted 35 sks class G cement from 1935' @ CIBP. to 1740' (cement plug of 195') Spot 20 BBL of 9.0 lbs 53 viscosity mud from 1740 to 674'. Set cement retainer @ 436' pumped 350 sks. class G cement circulated cement to surface out of Bradenhead. Closed Bradenhead and squeezed 50 sks cement into well bore. Spot cement from 436' to surface inside of casing. RDMO SU.

RECEIVED
MAY 4 1990
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED Alan A. Miller / MSW

TITLE AREA MANAGER

DATE 5/9/90

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

BLM-Farm (6), NMOGCC (5), Navajo Tribe, RSL, AAK, MLK, MAG

*See Instructions on Reverse Side