


LTR



Job separation sheet

(SUBMIT IN TRIPLICATE)

and Office **Sanle Fe**
Case No. **078-357**



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 24

19 62

Well No. **1** is located **1690** ft. from **N** line and **1650** ft. from **W** line of sec. **14**
34/4 Sec. **14** **27N** **9W** **14PK**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesaverte **San Juan** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6244** ft. (est.)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

It is our intention to Drill Well No. 1 to around 4600' to test Mesaverte formation.
Our casing program is as follows:

- 200' - 6-5/8" OD 24# J-55 Casing - To be cemented w/200 sacks cement. Cement to be circulated to surface.**
4600' - 4-1/2" OD 10.5# J-55 Casing - Cement in 2 stages as follows: 1st Stage: Cement w/250 sacks, 50% pozzol and 50% reg. w/2% gel and 12 1/2# fine Silicemite added per sack around casing shoe. 2nd Stage: A DV Tool will be run and set at a point below the Pictured Cliffs formation and 560 sacks 50% pozzol and 50% reg. cement will be pumped through tool to cover Pictured Cliffs formation and circulate to surface.

The designated Drilling Unit is 3/2 Section 14-27N-9W.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **WELLY OIL COMPANY**

Address **BOX 36**

HOBBS, NEW MEXICO

By

Title **Asst. Dist. Supt.**

CONSERVATION COMMISSION

AND ADDRESS DEDICATION STATE

LEASE

SECTION 14

TERMINATION

LINE 16

SECTION 14

14

DEDICATED ADDRESS OUTLINE

THE INTERESTS OF ALL

NO IF ANSWER

ALL THE OWNERS AND

brasscap
1967 SURVEY
U.S. D. L. M.

