


MAR 19 1956

Budget Bureau 42-R368.3.
Approval expires 12-31-65.Form 9-331a
(Feb. 1951)

(SUBMIT IN TRIPLICATE)

Land Office **Santa Fe**Lease No. **077971**Unit **P. A. Schultz**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico February 15, 1956

Well No. **1** is located **1300** ft. from **S** line and **1300** ft. from **W** line of sec. **15****SW/4 of Section 15**

(1/4 Sec. and Sec. No.)

T-27-N R-13-W

(Twp.)

(Range)

NMPH

(Meridian)

Wilcat

(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is **6032** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to plug the above well in accordance with the following:

- 1) Run tubing spot cement plug from PBD 5950' to 5850'.
- 2) Find free point, shoot 5 1/2" pipe and spot 25 sack cement plug on casing stub.
- 3) Recover 5 1/2" pipe.
- 4) Find free point, shoot 7-5/8" pipe and spot 25 sack cement plug on casing stub.
- 5) Spot cement plug 2850' to 3000'.
- 6) Spot cement plug 1850' to 1950'.
- 7) Spot cement plug 1305' to 1550'.
- 8) Spot cement plug 200' to 300'.
- 9) Recover 7-5/8" pipe.
- 10) Cement surface with 10 sacks, erect 4-foot pipe marker and restore ground level to original contours as per regulations.

Verbal approval received February 13, 1956, P. T. McGrath to J. M. Clark.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **STANOLIND OIL & GAS COMPANY**Address **P. O. BOX 487****FARMINGTON, NEW MEXICO**

By _____

Title **Field Superintendent**

DATE: 10-13-78
PAGE: 10-10-78

THE UNIVERSITY OF CHICAGO PRESS