

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

6. Lease Designation and Serial No.

SF-077875

8. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pipkin P. O. #4

9. API Well No.

3004506499

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

Pat Archuleta

3. Address and Telephone No.

P.O. BOX 800 DENVER, COLORADO 80201

303-830-5217

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1900' FSL

1770' FWL

K Sec. 17 T 27N R 10W

UNIT K

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☒ Other repair

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRUSU 2/7/97.

Set slick line plug at 6285'. Tag at 6485', sweep w/N2 foam and pull above perms, check for sand fill, found none.

Ran correlation log from 6200'-6429'. Shot limited entry perms at 6465', 6468', 6496', 6497', 6502', 6504', 6506' w/1 jsp, .340 inch diameter. Total 7 shots fired.

Did massive frac from 6465'-6506' w/ 526 bbls water and 495,709 scf of N2 to create a 70% quality foam, along with 21,868# of 20/40 Ottawa sand.

Flow test for 1 hr on 3/4 th choke, scip 1800, stip 1340.

Drill out dtts, tag sand at 6500', clean out sand to 6527' pbd and circ clean. Flowed for 5 hrs on .25 choke 370 scip, 260 sitp. Land tbq at 6432'.

14. I hereby certify that the foregoing is true and correct

Signed

Pat Archuleta

Title

Staff Assistant

03-27-1997

(This space for Federal or State office use)

ACCEPTED FOR RECORD

Approved by

Title

Conditions of approval, if any:

APR 9 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

FARMINGTON DISTRICT OFFICE