ror (F	eb. 19	951)		
			_	
	<b>-</b> -			X
		i		(

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office				
Lease No.	SF-079113			
Unit				
Jenkin	s Federal			

SUNDRY NO	TICES AND REP	ORTS ON WELLS
NOTICE OF INTENTION TO DRILL		T REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT	REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT		REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPA		REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		T REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CA		TARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		1.150001114
(INDICATE ABOV	E BY CHECK MARK NATURE OF REPOR	RT, NOTICE, OR OTHER DATA)
		March 28 , 19 61
Well No. is located is NEE SEC. 13	27K 124	ft. from killing of sec. 13
(½ Sec. and Sec. No.)	(Twp.) (Range) San Juan	(Meridian)
Basin Dakota (Field)	(County or Subdivision)	(State or Territory)
State names of and expected depths to object	DETAILS OF WO	enoths of proposed casings; indicate mudding jobs, cemen
, in the second	DETAILS OF WO	engths of proposed casings; indicate mudding jobs, cemen roposed work)
3/25/61 - Man Drilling Co	DETAILS OF WO	engths of proposed casings; indicate mudding jobs, cemen roposed work)
3/25/61 - Man Drilling Co	DETAILS OF WO live sands; show sizes, weights, and leng points, and all other important pompany, moved on locates. 10 3/4" Lone Staz 210 ax HA-5 2%, plug	engths of proposed casings; indicate mudding jobs, cemen roposed work)
3/25/61 - Man Drilling Co 3/26/61 - Ran 8 set 10 jt cemented with 2	DETAILS OF WO live sands; show sizes, weights, and leng points, and all other important pompany, moved on locates. 10 3/4" Lone Staz 210 ax HA-5 2%, plug	engths of proposed casings; indicate mudding jobs, cemen proposed work)  tion & spudded.  surface (32.50#) set at 296*KB
3/25/61 - Man Drilling Co 3/26/61 - Ran 8 set 10 jt cemented with 2	DETAILS OF WO live sands; show sizes, weights, and leng points, and all other important pompany, moved on locates. 10 3/4" Lone Staz 210 ax HA-5 2%, plug	engths of proposed casings; indicate mudding jobs, cemen roposed work)  tion & spudded.  surface (32.50%) set at 296 KB
3/25/61 - Man Drilling Co 3/26/61 - Ran & set 10 jt cemented with 2 Shut down for 1	DETAILS OF WO live sands; show sizes, weights, and leng points, and all other important property, moved on local ts. 10 3/4" Lone Staz 210 ax HA-5 2%, pluging repairs.	engths of proposed casings; indicate mudding jobs, cemen reposed work)  tion spudded.  surface (32.50%) set at 296 KB down, cament circulated.
3/25/61 - Man Drilling Co 3/26/61 - Ran & set 10 ji cemented with 2 Shut down for 1	DETAILS OF WO live sands; show sizes, weights, and leng points, and all other important property, moved on local table. 10 3/4" Lone Staz 210 ax HA-5 2%, plugging repairs.	engths of proposed casings; indicate mudding jobs, cemen roposed work)  tion spudded.  surface (32.50%) set at 296'KB down, cament circulated.
3/25/61 - Man Drilling Co 3/26/61 - Ran & set 10 ji cemented with 2 Shut down for 1 I understand that this plan of work must Southwest Pro- Company	DETAILS OF WO tive sands; show sizes, weights, and leng points, and all other important property, moved on local ts. 10 3/4" Lone Staz 210 ax HA-5 2%, plugging repairs.	engths of proposed casings; indicate mudding jobs, cemen roposed work)  tion spudded.  surface (32.50%) set at 296 KB down, cament circulated.
3/25/61 - Man Drilling Co 3/26/61 - Ran & set 10 ji cemented with 2 Shut down for 1 I understand that this plan of work must Southwest Pro-	DETAILS OF WO tive sands; show sizes, weights, and leng points, and all other important property, moved on local ts. 10 3/4" Lone Staz 210 ax HA-5 2%, plugging repairs.	engths of proposed casings; indicate mudding jobs, cemen reposed work)  tion spudded.  surface (32.50%) set at 296 %B down, cament circulated.
3/25/61 - Man Drilling Co 3/26/61 - Ran & set 10 jt cemented with a Shut down for a Lunderstand that this plan of work must Southwest Pro- Company	DETAILS OF WO tive sands; show sizes, weights, and leng points, and all other important property, moved on local ts. 10 3/4" Lone Staz 210 ax HA-5 2%, plugging repairs.	engths of proposed casings; indicate mudding jobs, cemen reposed work)  tion spudded.  surface (32.50%) set at 296 KB down, cament circulated.