



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____
Lease No. **NM-067853**
Unit _____
Collier Federal

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	X
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 29, 19**60**

Well No. **#1** is located **1850** ft. from **N** line and **790** ft. from **W** line of sec. **18**
NM/4 SW/4 Sec. 18 **27N** **12W** **NMPM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undes. (Dakota) **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

RECEIVED

JUL 1 1960

The elevation of the derrick floor above sea level is **5835** ft. **GL**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 6/18/60
Set 10 jts. 24" 8 5/8" surface casing at 330.36' RKB with 250 sx cement with 2% Calcium Chloride. Plug down 9:00 AM cement circulated.
6/28/60 TD 6040' RKB, set 186 jts. of 5 1/2" OD 15.5# J-55 casing at 6040' with 125 sx Pozmix 50/50 4% Gel, plus 75 sx laytex.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Southwest Production Company**
Address **162 Petroleum Center Bldg.**
Farmington, New Mexico

By *Carl W. Smith*
Title **Production Superintendent**