

BEKSON-MONTIN-GREER DRILLING CORP.

DRILLING HISTORY - #2 GINTHER

- 8- 7-59 Moved in and rigged up rotary. Spudded.
- 8- 8-59 TD 256' RKB. Set 8 joints 237' of 8-5/8" OD 24# J-55 casing at 249' with 200 sacks cement.
- 8- 9-59 Pressured up on casing to 500#. No pressure decrease in 30 minutes.
- 8-22-59 Drilled to TD 6033' RKB. Logged well. Set 188 joints 6035' of 5-1/2" OD 17# N-80 casing at 6033' with 75 sacks cement mixed 2% gel and 1/4# floccle per sack, plus 300 sacks cement mixed 1/4# floccle per sack. Temperature survey showed top of cement at 4000'.
- 9-13-59 Moved in and rigged up cable tools.
- 9-14-59
8-22-59 Pressured up on casing to 1000#. No pressure decrease in one hour. Cleaned out to 6012'. Perforated 5846-58', 5886-94', 5904-30', 5988-98' with 4 shots per foot. Sandfraced with 93,560 gallons water and 111,500# sand. Breakdown pressure 3800#, broke to 1500#, treating pressure 3500-4000#, average injection rate 59 barrels per minute. After injecting 55,000 gallons, dropped 53 rubber balls. No increase in pressure. After injecting 70,000 gallons dropped 64 rubber balls. Pressure increased approximately 100#. At end of treatment dropped 64 rubber balls, well balled off.
- 9-17-59 Found 50' of sand on top of plug. Attempted unsuccessfully to bail sand.
- 9-19-59 Killed well. Cleaned out sand. Ran 195 joints 2-3/8" OD EUE tubing with 1-10' sub, total string 5988', landed at 6000' RKB.
- 9-20-59 Reversed out water.
- 9-22-59 Shut well in for potential test.

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION

CONFIDENTIAL - SECURITY INFORMATION