

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
501 Airport Dr., Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1940' FNLX 1140' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

NOV 15 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in and rigged up service unit on 9-15-83. Spotted 36 cu. ft. Class B cement containing 2% CACL2 from PBD (6620') to 6364'. Spotted 30 cu. ft. Class B cement containing 2% CACL2 from 5576' to 5476'. Spotted 30 cu. ft. Class B cement containing 2% CACL2 from 3570' to 3470'. Spotted 30 cu. ft. Class B cement containing 2% CACL2 from 2053' to 1953'. Spotted 30 cu. ft. Class B cement containing 2% CACL2 from 950' to 1050'. Spotted 30 cu. ft. Class B cement containing 2% CACL2 from 421' to 321'. Spotted 18 cu. ft. Class B cement containing 2% CACL2 from 50' to 0'. Released the rig on 9-16-83.

RECEIVED

DEC 27 1984

Subsurface Safety Valve: Manu. and Type _____

OIL CON. DIV. ^{Set @} _____ Ft.
DIST. 3

18. I hereby certify that the foregoing is true and correct. District Administrative

SIGNED John Brown TITLE Supervisor DATE 11-9-83

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

*See Instructions on Reverse Side

NMOCC

APPROVED
AS AMENDED

DEC 21 1984

M. MILLENBACH
AREA MANAGER