

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF078094

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Fullerton Federal #2

9. API Well No.

3004506529

10. Field and Pool, or Exploratory Area

West Kutz P.C.

11. County or Parish, State

San Juan, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Bonneville Fuels Corporation

3. Address and Telephone No.

1660 Lincoln, Suite 1800, Denver, CO 80264 (303) 863-1555

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL, 1650' FEL, Sec 15, T27N, R11W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/10/97 MIRU. TOOH w/ 80 jts 1688' of 1" tubing. Tubing had parted, left 449' in hole. Notified BLM & Joe Ruybalid witnessed. Set Cmt retainer @ 1680'. Load back side, pump Plug #1 of 30 sx Cl-B neat cement to cover P.C. Stung out of retainer, left 6 sx cmt on top of retainer. Perforate 5 1/2" casing at 1125' with a total of 4 squeeze holes. On 10/11/97, set retainer @ 1075' and pump Plug #2 of 90 sx Cl-B cmt. Stung out of retainer and left 20 sx cement on top of retainer. PU and shot 2 holes at 166'. Pump Plug #3 of 80 sx Cl-B cement, circ cmt to surface inside 5 1/2" and in 5 1/2" x 10 3/4" annulus from 166'. Remover wellhead. Install dry hole marker. Rig released and well P&A 10/11/97.

Will notify BLM when surface ready for inspection.

RECEIVED
OCT 27 1997
OIL CON. DIV.
DIST. 3

070 FARMINGTON, NM
97 OCT 16 AM 11:24
RECEIVED
BLM

14. I hereby certify that the foregoing is true and correct *

Signed

Title

Operations Manager

Date

10/14/97

(This space for Federal or State office use)

Approved by

/S/ Duane W. Spencer

Title

Date

OCT 23 1997

Conditions of approval, if any: