



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Navajo
Alotted
Allottee L-149-Ind. 8446
Lease No. John Charles

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Report of Running of Packer</u> X
	<u>Report of Screens John #1 & #2</u> X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 22, 1959

John Charles
Well No. 6 is located 895 ft. from N line and 1030 ft. from E line of sec. 13
NE/4 Section 13 27N 9W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) MAY 25 1959
Klamath Mesa Verde Nat. Park San Juan New Mexico
(Field No.) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5776 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run & set Halliburton RTTS Packer, on 2" tubing, at 2172'. Packer would not hold. Pulled RTTS packer & ran Halliburton HES Packer on 2" tubing & tested top of 5 1/2" liner. Broke down & pumped into formation at 2200'.

SCREENS JOB NO. 1 around top of 5 1/2" liner at 2227' w/Halliburton HES packer set at 2183'.
w/50 sks. reg. cement. BDP 2200'. Max. pressure 2200'. Min. pressure 800'.

SCREENS JOB NO. 2 around top of 5 1/2" liner at 2227' w/Halliburton HES Packer set at 2183'.
w/50 sks. reg. cement, 90 sks. reg. cement 6% gal. & 2% CaCl. Put 90 sks. behind liner & left 10 sks. in 7-1/8" casing. BDP 1800'. Max. pressure 2500', Min. pressure 800'.
Screens & standing pressure 2500'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY
Box 426
Address Albuquerque, New Mexico

By (Signed) P. E. Cosper
Title District Superintendent