


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Lease Office Santa Fe
Lease No. SE 078357
Unit Marshall "A"



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<u>Production</u> X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Perforation and sand frac job</u>	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 6 is located 990 ft. from N line and 990 ft. from E line of sec. 14
NE 1/4 Sect. 14 27N 9E 104PM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Alamo Osaverde San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TO 4500'. Run 4-1/2" OD casing and set at 4487' with "DV" tool at 2180'. Cemented around shoe with 200 sacks, 50% pozzix and 50% regular cement, with 2% gal, 12 1/2# fine gilsonite per sack and 1/2# floccule per sack added. Temperature survey indicated top of cement behind casing at 3085'. Cemented through "DV" tool with 100 sacks, 50% pozzix and 50% regular cement, with 2% gel added. Perforated 4 1/2" OD casing with 4 Lane Wells Super Dyna Jet Xone shots per foot as follows: 4407-4424', 4398-4400', 4327-4379'. Sand water frac: Pumped down 4 1/2" OD casing, 50,000# of 20/40 sand and 50,000 gallons water. BHP 1300#. Max. T.P. 2000#. Min. T. P. 1750#. Flushed with 122 barrels water. Average injection rate 41.2 BPM. Shut down pressure 400#. Standing pressure in 10 minutes, 200#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY
Address Drawer 510
Farmington,
New Mexico
By _____
Title District Superintendent