B. & R. SERVICE COMPANY

TEMPERATURE SURVEY

WELL COUNTY AND STATE FRANCISCO COUNTY AND STATE	COMPANY				
SEC. TWP. RGE. 58 APPROX. TOP CEMENT Survey Begins at Approx. Fill-ty Max. Temp. Casing Size Casing Depth Trom to From to From to From to From to From Top Casing Survey Manual of Cement Amount of Cement Amount of Admix Recorded by REMARKS OR OTHER DATA TEMPERATURE IN DEGREES FAHRENHELE 1500 63° 999° 1200° 1200° 1406° 1406° 1200° 1406° 1400°					
Survey Begins at Approx. Fill-Up					
Survey Begins at Approx. Fill-Up Max. Temp. Log Measured From Run No. 1 Casing Size Casing Depth Dium of Hole From to				KGE	. ćX
Approx. Fill-Up	APPROX. TOP				
Casing Size	_				
True					
1500 60° 90° 100° 120° 140°	_	Casing Depth			Depth
Date of Cementing Time 1.23 1.75 1	· · · · · · · · · · · · · · · · · · ·				
Amount of Cement Amount of Admix Recorded by REMARKS OR OTHER DATA TEMPERATURE IN DEGREES FAHRENHELD 1500 62° 93° 103° 123° 143° 1220 1420° 2220 2220 2220 2220 2220 2220 2220		· · · · · · · · · · · · · · · · · · ·			
Amount of Admix Recorded by REMARKS OR OTHER DATA TEMPERATURE IN DEGREES FAHRENHELT 1500 60° 99° 103° 120° 140° 1500 200 200 200 200 200 200 200 200 200	•				
TEMPERATURE IN DEGREES FAHRENHELT 1500 60° 90° 100° 120° 140° 1500 200 200 200 200 200 200 200 200 200					
TEMPERATURE IN DEGREES FAHRENHELT 1500 60° 50° 170° 170° 140° 1500 60° 170° 170° 140° 1500 200 170° 170° 140° 200 170° 170° 140° 200 170° 170° 170° 140° 1500 200 170° 170° 170° 140° 1500 200 170° 170° 170° 170° 170° 170° 170° 17	Recorded by	GERTAL POER	Witnessed by	W. 7.	JUNEAUN
TEMPERATURE IN DEGREES FAHRENHELT 1500 60° 60° 100° 100° 140° 1500 200 200 200 200 200 200 200 200 200		REMARKS OF	OTHER DAT		
1500_60°				OIL CON	01956
1500_60° 30° 120° 140° 1600 1700 ANGUALY 1725' 1800 2000 2100 2200 2400 2600 2600 100				Ols	COM James
1700 ANDMALY 1723* 1800 2000 2100 2200 2500 2600 2700 2600 Till Surveyed 2812*	TEMPERA	ATURE IN D	EGREES FA	HRENH	ELF
1700 ANDMALY 1723* 1800 2000 2100 2200 2500 2600 2700 2600 Till Surveyed 2812*					
1700 ANDMALY 1723* 1800 2000 2100 2200 2500 2600 2700 2600 Till Surveyed 2812*					To the control of the
1700 ANOMAL 7 1725 1900 2000 2100 2200 2500 2600 2700 2000 T.C. SURVEYED 28121	1500 60°	80°	1909	120 %	140°
1700 ANOMAL 7 1725 1900 2000 2100 2200 2500 2600 2700 2000 T.C. SURVEYED 28121					
ANOVALY 1725' 1800 2000 2100 2200 2500 2600 T.C. SURVEYED 2812'	1500				
ANOVALY 1725' 1800 2000 2100 2200 2500 2600 T.C. SURVEYED 2812'					
ANOVALY 1725' 1800 2000 2100 2200 2500 2600 T.C. SURVEYED 2812'					
1900 2000 2100 2200 2400 2500 2600 2700 2600	1700	ANOREM: VI 1770			
2000. 2100. 2200. 2300. 2400. 2500. 2600. 2700. 2800. T.E. SURVEYED 28121.		ANOMALI 172	1		
2000 2200 2300 2400 2500 2600 2700 2800 7.1. SURVIYED 28121	1800.				
2000 2200 2300 2400 2500 2600 2700 2800 7.1. SURVIYED 28121					
2000 2200 2300 2400 2500 2600 2700 2800 7.1. SURVIYED 28121					
2200 2300 2400 2500 2600 2700 2800 7.5. SURVEYED 28121	1900			or continue	
2200 2300 2400 2500 2600 2700 2800 7.5. SURVEYED 28121					
2200	2000				
2200					
2200					
2400 2500 2600 2700 2812*	2100.		100 to \$1.0 to	e name promi e e e e e e e e e e e e e e e e e e e	<u> </u>
2400 2500 2600 2700 2812*			The state of the s		
2500 2600 2700 2800 T.E. SURVEYED 28121	2200			and the second s	
2500 2600 2700 2800 T.E. SURVEYED 28121					
2500 2600 2700 2800 T.E. SURVEYED 28121	2311				
2500 2700 2800 7.5. SURVEYED 2812*					
2500 2700 2800 7.5. SURVEYED 2812*					
2700 28121	2400	,		, de l'agresió ,	and the second s
2700 28121					
2700 28121	2500				;
2700 T.E. SURVEYED 28121					
2700 T.E. SURVEYED 28121					
2800 T.E. SURVEYED 2812*	2600				
2800 T.E. SURVEYED 2812*					
2800 T.E. SURVEYED 2812*	2700				
T.D. SORVEYED 2812				: 1	
T.D. SORVEYED 2812					•
290?	.2600	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	o. SURVEYER	28121	
290?			,		
	290?			e de la composiçõe de la c	

