| Form 9-331a<br>(Feb. 1951) |  |  |  |  |  |
|----------------------------|--|--|--|--|--|
|                            |  |  |  |  |  |
|                            |  |  |  |  |  |
|                            |  |  |  |  |  |
|                            |  |  |  |  |  |

(SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Lease No. NN 050402-A
Unit Pairfield

| SUNDRY NOTICES AN                | D REPORTS ON WELLS EGE VE   |
|----------------------------------|---|
| NOTICE OF INTENTION TO DRILL     | SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY |
| (INDICATE ABOVE BY CHECK MARK NA | TURE OF REPORT, NOTICE, OR OTHER DATA)  |

| (INDICATE.                               | ABOVE BT OTTEN   | May 15   | , 19 <b>61</b>               |
|--|--|--|------------------------------|
|  | 1 1100 ft. from. \bigg\{\mathbf{N}} \\ \mathbf{X} \end{ar}                       | nd 990 ft. from $\left\{ egin{array}{c} E \\ \mathbf{w} \end{array} \right\}$ (Meridian) | line of sec.                 |
| MR. NR. Sec. 14<br>(½ Sec. and Sec. No.) | (Twp.) (Range)   | New Ma   | MELLITY                      |
| (Field)                                  | (County or Subdivision)  | (State or  | MAY 1 8 1961                 |
| The elevation of the derrick f           | loor above sea level is <b>5856.</b>   | <b>∮</b> ft.   | OIL CON. COM.<br>DIST. 3     |
|  | DETAILS OF WO  | RK   | DIST. 3                      |
| (State names of and expected depths to o | objective sands; show sizes, weights, and<br>ing points, and all other important | lengths of proposed casings; ind<br>proposed work)                                       | icate mudding Jobs, cellions |

Drilled to 6145' (I-EL). Nam Welex I-EL & Acoustic Velocity logs. Set 6133.67' of 4 1/2", J-55, 9.50% and 11.60% casing at 6144.17', cemented with 250 sacks of Portland cement plus 4% gel. Plug down at 5:30 A.M. 5-28-61. Ram McCullough correlation and cement log. Perforated 6001-6023 (X-EL) with 2 casing jets per foot. Well kicked off and cleaned up. Ram 192 joints of 2 3/8" 4.7% J-55 tubing, set at 6034.03'.

| I understand that this plan of work must receive approval in writing by the C | seological Survey before operations may be commenced. |
|---|---|
| Company W. H. Hadeon  |   |
| Address 1126 Mercantile Securities Bldg.                                      | ON A Am A   |
| Dallas 1, Texas   | By  |
|   | Title Geologist  GPO 862040                           |