

Form 3160-5  
(June 1990)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTRECEIVED  
BLMFORM APPROVED  
Budget Bureau No. 1004-0135 -  
Expires: March 31, 1993

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir:  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. SF 078009-C
2. Name of Operator Dugan Production Corp.	6. If Indian, Allottee or Tribe Name 34
3. Address and Telephone No. P.O. Box 420, Farmington, NM 87499 (505) 325-1821	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 990' FNL & 990' FWL 18 - 27N - 13W	8. Well Name and No. Rex 2
	9. API Well No.
	10. Field and Pool, or Exploratory Area Undesignated Gallup
	11. County or Parish, State San Juan, N.M.

## 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other Amend P&A Procedure
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Replace 8.34 lb./gal., 40 viscosity mud with water as plugging fluid to separate cement plugs. Virgin reservoir pressure of the Gallup is 1600 psi, and the Pictured Cliffs - Fruitland is 250 psi in nearby fields. Fresh water will provide adequate hydrostatic pressure to control these zones.

If unable to load hole so that plugs may be balanced, request permission to set a cast iron bridge plug at Gallup top and spot 50' cement on top.

14. I hereby certify that the foregoing is true and correct

Signed John Alexander  
(This space for Federal or State office use)Title Operations ManagerDate 9/2/93Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

APPROVED

SEP 08 1993

DISTRICT MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fraudulent or misleading statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

NMOOD