

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

Section 10

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records. *P E*

Signed

The summary on this page is for the condition of the well at above date.

Commenced drilling May 14, 1956 Finished drilling May 28 1956

(Denote gas by G)

REL TO
to
OH CO to
IS OH
to

No. 1, from None to _____

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

[illegible]

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8"	147'	150	Circulated		
5-1/2"	2209'	150	Halliburton		

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

~~Fractured - sand & water~~

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
Fractured through perforations from 2092' to 2150' with 50,000# sand and 46,200 gals. water. E.D. 2300# - T.P. Max. 1450# - Min. 1500#. Injection rate 58 BPM						

Rotary tools were used from 0 feet to 2210' feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

_____, 19_____ Put to producing _____, 19_____

The production for the first 24 hours was ----- barrels of fluid of which ----- % was oil; ----- % emulsion; ----- % water; and ----- % sediment. Gravity, °Bé. -----

If gas well, cu. ft. per 24 hours 100000 Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. **SITP 600# - SICP 600#**
EMPLOYEES

Barron Drilling Company Driller _____, Driller _____
 _____, Driller _____, Driller _____

FROM--	TO--	TOTAL FEET	FORMATION
0'	2091'	2091'	Sand and shale
2091'	2151'	60'	Pictured Cliffs
2151'	2210'	59'	Lewis
Total Depth 2210'			
Plug Back Total Depth 2177'			

