

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan
Initial X Annual _____ Special _____ Date of Test 4-9-61
Company Pan American Petroleum Corp. Lease E. H. Pipkin Well No. 11
Unit M Sec. 12 Twp. 27N Rge. 11W Purchaser Southern Union Gas Company
Casing 4-1/2" Wt. 9.5 I.D. 4.090 Set at 6441 Perf. 6311 To 6335
Tubing 2-3/8" Wt. 4.7 I.D. 1.995 Set at 6311 Perf. open ended at 6311 To _____
Gas Pay: From 6311 To 6335 L 6311 xG .700 (est) GL 4432 Bar.Press. 12
Producing Thru: Casing _____ Tubing X Type Well Single gas
Single-Bradenhead-G. G. or G.O. Dual _____
Date of Completion: 4-9-61 Packer None Reservoir Temp. 142° F

OBSERVED DATA

Tested Through (Packer) (Choke) (Meter) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Packer) (Line) Size	(Choke) (Choke) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI	<u>24 days shut in</u>					<u>2031</u>		<u>2031</u>		
1.	<u>2"</u>	<u>27"</u>	<u>183</u>			<u>268</u>	<u>60 (est)</u>	<u>712</u>	<u>60 (est)</u>	<u>3 hr.</u>
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.365</u>		<u>185</u>	<u>1.000</u>	<u>0.9250</u>	<u>1.023</u>	<u>2284</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2043 P_c 4,173,849

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.						<u>524,176</u>	<u>3,649,673</u>		
2.									
3.									
4.									
5.									

Absolute Potential: 2526 MCFPD; n .75

COMPANY Pan American Petroleum Corporation


ADDRESS Box 488, Farmington, New Mexico

AGENT and TITLE E. H. Bauer, Jr., Senior Petroleum Engineer

WITNESSED _____

COMPANY _____

REMARKS _____



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .