

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Southland Royalty Company
3. ADDRESS OF OPERATOR  
P.O. Drawer 570, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FSL & 990' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED  
NOV 08 1982  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
SF - 080382
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Schwerdtfeger
9. WELL NO.  
#1
10. FIELD OR WILDCAT NAME  
West Kutz Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 8, T27N, R11W
12. CCUNTY OR PARISH San Juan 13. STATE New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6142GL

RECEIVED  
DEC 27 1984

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)

OIL CON. DIV.  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-01-82 Picked up 2-3/8" work string and spotted 27 sacks cement plug from TD to 1790'. Pulled up and spotted 11 sacks cement plug from 1647' to 1547' to cover Fruitland Top at 1597'.

11-2-82 Perforated 5-1/2" casing at 794' and squeezed behind pipe to 694' with 35 sacks. Spotted 11 sacks in casing from 794' to 694' to cover Ojo Alamo top at 744'. Spotted 18 sacks cement plug from 157' to surface to cover surface casing shoe. Squeezed bradenhead with 50 sacks cement.

11-3-82 Cut off casing 4' below surface, covered and cleaned location.

NOTE; Well is in NIIP; therefore no dry hole marker was installed.  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineer DATE November 4, 1982

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

NMOCC  
See Instructions on Reverse Side

APPROVED  
AS AMENDED

DEC 21 1984

M. MILLENBACH  
AREA MANAGER