Form 3160-5 (November 1994)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

## FORM APPROVED Budget Bureau No. 1004-0135 Expires July 31, 1996 5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELL	/FI I 9	NW	ON	REPORTS	AND	NOTICES	SUNDRY
------------------------------------	---------	----	----	---------	-----	---------	--------

NMSF-080382-A

Do not use this form for	6. If Indian, Allottee or Tribe Name				
abandoned well. Use Fort	TI 3 160-3 (APD) for SL	ICA PT POSECE	WE	<b>1</b>	
SUBMIT IN TRIPLICATE -	Other instructions on	reverse side	0 1000	7. If Unit or CA/Agi	eement, Name and/or No
1. Type of Well Oil X Gas Well Other		Onn on	3 1330 <b>-</b>	8. Well Name and N	0.
2. Name of Operator		<del></del>		Schwerdtfeger	No. 2
Marathon Oil Company 3a. Address	1 25	DIST.	3	9. API Well No.	
P.O. Box 2490, Hobbs, NM 88240		. Phone No. (include area co 05) 393-7106	1e)	30-045-06666 10. Field and Pool, o	r Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Descrip				Basin Dakota	Exploratory Alea
UL I, Section 8, T-27-N, R-11-W 1850' FSL and 790' FEL				11. County or Parish	State
				San Juan Co.	NM
12. CHECK APPROPRI	ATE BOX(ES) TO INDIC	CATE NATURE OF NOT	CE, REPORT	OR OTHER DATA	
TYPE OF SUBMISSION		TYPE	OF ACTION		
X Notice of Intent	Acidize	Deepen	Production	(Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	Reclamatic	on 🔲	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplet	te 🔲	Other
Final Abandonment Notice	Change Plans	Plug and Abandon	X Temporari	ly Abandon	
	Convert to Injection	Plug Back	Water Dis	posal	
Marathon Oil Company request appr The procedure to perform this wor 1. MIRUPU. ND wellhead and NU B 2. RIH with tubing to 2500'. 3. Circulate inhibited fluid int 4. Perform casing integrity test 5. POOH with tubing, laying down 6. ND BOP and NU wellhead. 7. RDMOPU.	consist of:  OP.  o well.	NOV 0 1 199	nis well h		
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) Thomas P. Kacir			on Engine	er	
1 Koma & Kaus		Date 10/05/98		-	
<del></del>	SPACE FOR FEDER		E USE	Legi	1.0.1005
Approved by /S/ Duane W. Spencer		Title		961	1 6 1998
Conditions of approval, if any, are attached. Approval of certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations thereon.					
Title 18 U.S.C. Section 1001, makes it a crime for any fraudulent statements or representations as to any matter within	person knowingly and willists jurisdiction.	fully to make to any depar	ment or agenc	y of the United States	any false, fictitious or

## WELLBORE STATUS

Schwerdtfeger No. 2 UL I, 1850' FSL, 790' FEL Section 8, T-27-N, R-11-W San Juan County, NM API # 30-045-06666 Federal Lease # NMSF-080382-A

JAN 1961: Drill to 6594'.

Ran & cmt'd 4 1/2" csg to 6593'.

Perfed 6550'-6565' w/ 4 JSPF.

Frac w/ 40,000 gals water

and 20,000 # 20/40 sand.

Cut 3 slots at 6495'-6502', 6507'-6512', 6516'-6520'. Frac 6495'-6520' with 28,000 glas water and 25,000 # 20/40 sand.

Perfed 6444'-6460' w/ 4 JSPF. Frac 6444'-6460' with 36,000 gals water and 18,000 # 20/40 sand.

JAN 1969: Install Packer.

FEB 1991: Acidized w/ 2500 gals.

JUN 1998: Parted tubing at 4127'. Freepointed tbg and found tbg free at 4152'.

OCT 1998: Ran tapered swage to 3794'.
Ran bit to 3830'. Ran pkr.
Found top of csg leak at 2839'.
Pumped 110 sks of cmt at 3805'.
Tagged cmt at 3254'.
Set cmt retainer at 2825'.
Pumped 55 sks cmt below retainer.
Pumped 10 sks cmt above retainer.

Perforations:

6444' - 6460' 4 SPF 6495' - 6502' Cut 3 Slots 6507' - 6512' Cut 3 Slots 6516' - 6520' Cut 3 Slots 6550' - 6565' 4 SPF

PBTD: 6578'



8 5/8", csg set at 205". Cemented w/ 175 sks, did not circulated. Pumped 35 sks down annulus.

10 sks of cement Cement Retainer @ 2825' 55 sks of cement

Pumped 110 sks cement plug from 3805' to 3254'

JUNE 1998: Fish left in hole consist of 2260' of 2-3/8" tbg, SN, 31' of 2-3/8" tbg, Baker Mod 'G' pkr.

4 1/2", 11.6#/ft, J-55 casing set at 6593'. 1st stage cmt'd w/ 150 sks. 2nd stage cmt'd w/ 75 sks.