Form C-122

				MULTI-	POINT B	ACK PRES	SSURE TES	T FOR GAS	S WELLS		Revised 12-1-5	5
Pool South Blanco Fo					ormation Plotured Cliffs				_County_		en Juan	
Initia	[nitial			Special				Date of Test		6/5/30	_	
Company Astro CEL & Company				Lease Whitley			ay	Well No. 4				
Casing 2 7/8 Wt. 6.5 I.D. 2.								-				
Tubing Wt. I.D.												
											ess. 11	
												_
Date	of Comple	tion	~		Packe	n	Sin	gle-Brade	enhead-G.	G. or	G.O. Dual	_
Date C	or compre	01011			racke			neserve	orr remb.		~	_
							ED DATA					
Tested Through (Choke)					Mahama			Type Taps				_
			Flow Da				Tubing		Casing I			
No.	(\mathtt{Line})	(Ori	fice)	}	Į	_	Press.				of Flow	
SI	Size	S:	ize 	psig	h _w	°F.	psig	°F.	psig	F•	 	_
$\frac{S_1}{1.}$		 -					 		139	1	7 sl	
2.											3.000	
3.												_
5.		 					 			 		_
						ET ON CAT	CULTATION	c	+	· 		_
	Coefficient Pre				FLOW CALCULATIONS essure Flow Temp. Gravity				Compre	ess.	Rate of Flow	_
No.	(24-Hour) $\sqrt{h_W}$			1		Factor F _t					Q-MCFPD @ 15.025 psia	
1.	12,355		A M. 1		151	1.00		F _g	1.024		1810	
2.												_
1. 2. 3. 4.			 									_
5.												_
					PR	ESSURE C	CALCULATI	ONS				
as Lic	wid Hydr	oca rboi	n Ratio	0		cf/bbl.		Speci	ific Grav	itv Sena	arator Gas	
Fravity of Liquid Hydrocarbons				deg. Spec				ific Gravity Flowing Fluid			_	
'с			(l-e ^{-s})			-	Pc	618	Pc	351.	_
		 		 -								_
No.		P	E F	_c Q	$(F_cQ)^2$	(F	$\left(\frac{1}{2}c^{Q}\right)^{2}$	$P_{\mathbf{w}}^2$	$P_c^2 - P_w^2$		Pw Pc	
	Pt (psia)				(1-e o)			23.4		P _w P _c		
2. 3. 4.		Ţ <u> </u>										_
3.		 									_	
5.												_
COMPAN ADDRES	SS	Personal	1 1.				Loo	0,85				
WITNES		E OR	IGINAL S	SIGNED BY	Y L. M. STI	EVENS	<u>L</u>	, H. Stev		A ANGLE		_
COMPAN	11			<u> </u>		REN	MARKS					
							*	2	1 12 31			



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure ($P_{\rm W}$). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pwt Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{nv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_W cannot be taken because of manner of completion or condition of well, then P_W must be calculated by adding the pressure drop due to friction within the flow string to P_+ .

STATE OF THE PLANCO

OF CORD INVALIDATION OF ARRESTOR

AZTEC DISTRICT OFFICE

REMONE OF CORDS INCOME.