Form 9-331 a (Feb. 1951)

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Santa Fe
Lease No	SF 079596
Unit G.	M. Morris
	Unit

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLA	ANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER	R SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OF		
NOTICE OF INTENTION TO SHOOT OR		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR AL		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON W	/ELL	
(INDICATE	E ABOVE BY CHECK MARK NA	NTURE OF REPORT, NOTICE, OR OTHER DATA) U.S. GEOLGGICAL STREET
C. M. Morris Gas U		Farmington, New Mexico, December 29, 1959
· =		(N) 13300 c ( <b>E</b> ) 30
Well No. is locate	ed 1190 ft. from	$\left\{\begin{array}{c}N\\\mathbf{S}\end{array}\right\}$ line and 1190 ft. from $\left\{\begin{array}{c}\mathbf{X}\\\mathbf{W}\end{array}\right\}$ line of sec. 10
MM/4 NW/4 Section 10	T-27K R-	LOW N.X.P.M.
(1/4 Sec. and Sec. No.)  Angels Peak Dakots	(Twp.) (Ra	ange) (Meridian) <b>Ray Hexico</b>
(Field)	(County or S	
Spudded 12-1/4" ha	objective sands; show sizes, ing points, and all othe	S OF WORK  weights, and lengths of proposed casings; indicate mudding jobs, comenter important proposed work)  lights, and drilled to 2361. 9-5/89  of cament containing two percent casaium
Spudded 12-1/4" he casing was set at 236; chloride. Coment circumster shutoff with 800	objective sands; show sizes, ing points, and all oth ole on December with 120 snoks ulated. After worst for 30 minus	, weights, and lengths of proposed casings; indicate mudding jobs, cementer important proposed work)
Spudded 12-1/4* he casing was set at 236* shloride. Coment circumster shutoff with 800 pressure drop. Reduced I understand that this plan of work Pan American Company	objective sands; show sizes, ing points, and all oth color on Docember with 120 sacks plated. After a psi for 30 minud hole to 7-7/8*	weights, and lengths of proposed casings; indicate mudding jobs, cementer important proposed work)  11, 1959, and drilled to 236'. 9-5/8* of cement containing two percent calcium sating on cement, tested casing and ites which held with no indication of at 236' and resumed drilled.  JAN 4 1960 OIL CON. COM. DIST. 3  writing by the Geological Survey before operations may be commenced.
Spudded 12-1/4* he casing was set at 236* chloride. Coment circu water shutoff with 800 pressure drop. Reduced	objective sands; show sizes, ing points, and all oth color on Docember with 120 sacks plated. After a pai for 30 minuted hole to 7-7/8**  must receive approval in we receive approval	weights, and lengths of proposed casings; indicate mudding jobs, cementer important proposed work)  Li., 1959, and drilled to 236'. 9-5/8* of cement containing two percent calcium saiting on cement, tested casing and ites which held with no indication of at 236' and resumed drilled.  JAN 4 1960 OIL CON. COM. DIST. 3  writing by the Geological Survey before operations may be commenced.

