

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
R & G DRILLING COMPANY
3. ADDRESS OF OPERATOR c/o Walsh Engr. & Prod.
P.O. Drawer 419, Farmington, N.M. 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 900'FNL, 900'FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

MAR 3 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SEE ATTACHED

RECEIVED
OIL & GAS
DIST. 3

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

FOR: R & G DRILLING COMPANY
18. I hereby certify that the foregoing is true and correct

SIGNED Dwayne Blanchett TITLE Walsh Engr. & Prod. Corp. DATE 3/2/83
Production Foreman

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

MAR 07 1983
James F. Smith
DISTRICT ENGINEER

*See Instructions on Reverse Side

NMOCC



R & G DRILLING COMPANY
SCHLOSSER NO. 12
PLUGGING PROCEDURE

8-5/8", 24.0 lb., set at 90 feet with 50 sacks.
Top of Cement - Surface

5-1/2", 14 lb., set at 2108 feet with 200 sacks.
Calculated top of cement in 7-7/8" hole - 745'.

Perforations: 2035' - 2068'

Well will be plugged in the following manner:

1. No casing will be pulled.
2. Spot cement plug from 2068' to 1968' - 11 sacks.
3. Spot cement plug from 1823' - 1723' (Fruitland) - 11 sacks.
4. Spot cement plug from 985' - 885' (Ojo Alamo) - 11 sacks.
5. Spot surface plug at 140' - 16 sacks.
6. Set surface marker.
7. Clean up location and rehabilitate to BLM stipulations.