

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

95 AUG 15 PM 3:01

1. Type of Well
GAS

RECEIVED
AUG 21 1996

070 FARMINGTON, NM

5. Lease Number
NM-84078
6. If Indian, All. or
Tribe Name

2. Name of Operator
MERIDIAN OIL

OIL CON. DIV.
DIST. 3

7. Unit Agreement Name

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
Thompson C #2

9. API Well No.
30-045-06807

4. Location of Well, Footage, Sec., T, R, M
990' FSL, 990' FEL, Sec. 2, T-27-N, R-12-W, NMPM

10. Field and Pool
West Kutz Pict. Cliffs

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

8-5-96 MIRU. ND WH. NU BOP. TOO H w/76 jts 1" tbq. TIH w/5 1/2" gauge ring to 1600'. TOO H. TIH w/5 1/2" cmt retainer, set @ 1598'. TOO H. Circ hole clean w/28 bbl wtr. PT csg to 500 psi/5 min, OK. Establish injection into Pictured Cliffs open hole. Plug #1: pump 30 sx Class "B" cmt below cmt retainer into Pictured Cliffs open hole, pump 39 sx Class "B" cmt above cmt retainer, TOC @ 1254'. TOO H. TIH, perf 3 sqz holes @ 630'. TOO H. TIH, attempt to establish injection (Verbal approval to change plans from Joe Sanchez, BLM). TIH to 685'. Pump #2 pump 40 sx Class "B" cmt inside csg @ 332-685'. TOO H to 163'. Establish circ down csg & out bradenhead. Plug #3: pump 24 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. SDON.

8-6-96 ND BOP. Cut off WH. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 8-6-96.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 8/12/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

P O E D

AUG 16 1996

John Spence

M1000