

Navajo

(SUBMIT IN TRIPLICATE)

U. S. Land Office

UNITED STATES

Lease or permit No.

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee

Lease No. **Tract B**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Shiprock, New Mexico. March 5, 1940

Well No. **8A** is located **1640** ft. from **S** line and **1720** ft. from **W** line of sec. **3**

SW 1/4 sec 3 **27N** **17W** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Table Mesa **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **5355** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Cemented Dakotas, 1420' to 1330', with 10 sacks cement dumped from bailer; ripped and pulled 1036' 11" of 5 3/16" 17# 11 1/2 T casing, filled hole with shale mud to 650', ~~ripped and pulled~~ ripped and pulled 551' 5" of 6 5/8" 20# 10 T casing and 547' 1" of 8 1/4" 32# 10 T casing; cemented with 10 sacks Calseal pumped down thru 2" tubing 650' to 595', filled with mud to 500', cemented with 10 sacks Calseal thru tubing 500' to 475', filled with mud to 75', dumped 5 sacks Calseal 75' to 62', filled with mud to 6', cemented 10' of 6 5/8" casing 6' above ground level in top center of 12" conductor pipe left in hole. Completed abandonment February 28, 1940.

Casing left cemented in hole: 362' of 5 3/16" from 1399' to 1037', 767 1/2' of 6 5/8" from 1319' to 551 1/2', 78' of 8 1/4" from 525' to 547', 49' of 12 1/2" from 49' to surface.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Continental Oil Company**

Address **Shiprock, New Mexico**

By **George Cox**
George Cox
Title **Superintendent**