


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 3F-046563  
Unit Fred Feasel "G"



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Fred Feasel "G"

Farmington, New Mexico September 4, 1959

Well No. 1 is located 1890 ft. from S line and 1890 ft. from W line of sec. 2

NE/4 SW/4 Section 2  
(1/4 Sec. and Sec. No.)

T-27-N  
(Twp.)

R-10-W  
(Range)

N.H.P.M.  
(Meridian)

Angels Peak Dakota  
(Field)

San Juan  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 5973 ft. (Ground Level)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Total depth 6560'. 4-1/2" casing was set at 6552' with 2-stage cement tool at 2164'. Cemented first stage with 400 sacks 6% gel cement containing 1-1/2 pounds Taf-Plug per sack followed by 100 sacks neat cement. Tested casing with 3000 psi for thirty minutes which held with no indication of pressure drop. After waiting on first stage cement, cemented second stage with 250 sacks 4% gel cement. Tested casing with 3000 psi for thirty minutes which held with no indication of pressure drop. Drilled 2-stage cement tool at 2158, drilled cement 6515-6518'. Tested casing with 1000 psi for thirty minutes which held with no indication of pressure drop. Left tubing and bit in hole. Released rotary rig on September 2, 1959. Preparing for completion operations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487

Farmington, New Mexico

Attn: L. O. Speer, Jr.

ORIGINAL SIGNED BY  
R. M. Bauer, Jr.

By

Area Engineer

Title