

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

Sundry Notices and Reports on Wells

1. Type of Well
GAS

93 JUN 21 PM 4:50

Lease Number
SF-078050

070 FARMINGTON, NM

If Indian, All. or
Tribe Name

2. Name of Operator
MERIDIAN OIL

7. Unit Agreement Name

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
Turner Hughes #7

9. API Well No.

4. Location of Well, Footage, Sec., T, R, M
2300'FNL, 890'FWL Sec.4, T-27-N, R-9-W, NMPM

10. Field and Pool
S.Blanco Pic.Cliff

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

06-16-93 MOL&RU. Blow to pit. TOOH w/1" tbq. Ran scraper to 2200'. Set cmt ret @ 2154'.

06-17-93 Cmt plug 2532-2104' w/86 sx Class "B" below ret, 5 sx above. Pull to 2060'. Circ w/35 BW. PT csg 500#, leak @ 1 BPM @ 500#. Spot 8 bbl 8.4# 40 vis mud, displace 2060-1715'. Pull to 1627'. Perf 4 holes @ 1715'. Set ret @ 1627'. Est inj rate. Cmt plug #2 1715-1203'. Squeeze 84 sx under ret, 48 sx above ret. Pull to 1063'. Spot 14 bbl 8.4#, 40 vis mud 1063-448'. PT csg 500#, leak 1 BPM @ 500#. LD to 374'. Perf 4 holes @ 448'. Set cmt ret @ 374'. Est inj rate 2 BPM @ 500#. Cmt plug #3 448-321' w/41 sx below ret, 6 sx above. Pull to 251'. Spot 3 bbl 8.4# 40 vis mud 374-146'. TOOH. Perf 2 holes @ 146'. Set surface plug 146-surface. Circ 68 sx cement until flowed out bradenhead. Cut off WH. Install dry hole marker. Released rig. Well plugged & abandoned.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 6/18/93

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date _____

CONDITION OF APPROVAL, if any: Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

APPROVED

JUN 22 1993

DISTRICT MANAGER

NMOCD