STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	URLINGTON R	ESOURCES	OIL & GAS CO.	. 1-7-207-	Lease	FRONTIER B			Well No. 3	
Location	•	0	T		Dan	044144	Country	0.441.111.4.41		
of Well:	Unit E		4 Twp. ESERVOIR OR POO	_027N L	Rge.	O11W YPE OF PROD. (Oil or Gas)		SAN JUAN HOD OF PROD. ow or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)	
Upper Completion	GALLUP	-				Gas		Flow	Casing	
Lower Completion	DAKOTA					Gas		Flow	Tubing	
				LOW SHUT-IN				T =		
Upper	Hour, date shut-in 9/17/99		Length of time shut-in			SI press. psig		Stabilized? (Yes or No)		
Completion			72 Hours		0				_	
Lower Completion	9/17/9	9	24 Hou			442				
				FLOW TE	ST NO.		<i>a</i>			
	at (hour,date)*		9/18/99	8/99 PRESSURE		Zone producing	(Upper or	Lower) LO	WER	
TIME	LAPSED	<u></u>		Lower Comp	lation	PROD. ZONE TEMP	1	REMARKS		
(hour,date)	SINC	*	Upper Completion	Lower Comp.	leuon	TEMP		REIV	IARNS	-
9/19/99	48 Ho	urs	0	222			gallu	gallup t/a		
9/20/99	72 Hours		0 222							<u> </u>
			:							
									301 27 W	
Production rat	e during test									
Oil:	BOPD based on		Bbls. in		Hours.		Grav.		GOR	
Gas:		I	MCFPD; Tested thru (Orifice or Mete	r): 					
			MID-	TEST SHUT-IN	PRES	SURE DATA				
Upper Completion	Hour, date shut-in Length of time shut-in		-in	SI press. psig			Stabilized? (Yes or No)			
Lower Completion	i i		Length of time shut-in		SI press. psig			Stabilized? (Yes or No)		

			ELOW TEST NO.	2	- ·· · · · · · · · · · · · · · · · · ·			
Commenced at (hour, date) [™] Zone producing (Upper or Lower):								
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE TEMP.	REMARKS			
(1.041) 44(4)	51102	Upper Completion Lower Complet		IEMP.				
Production rate dur	ring test							
Oil:	BC	OPD based on	Bbls. in	Hours	Grav	GOR		
Gas:		MCFPE): Tested thru (Orific	ce or Meter):				
Remarks:								
	·							
I hereby certify that	t the information her	rein contained is true	and complete to the	best of my knowledg	e			
		2 7 199 9 19						
Approved			· o	perator Burlingto				
New Mexico Oi	l Conservation Divi	sion	В	y Alono L	las			
By	INAL SIGNED ET. (TOPLE T. PERFAM	Т	itle Operations As	Đ			
-	TERRET Y OIL & GA	AS INSPECTOR, DIS	ī. 4 3		- 10-			
Title			D	ate Friday, Octob	er 08, 1999			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Tes. No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except.

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).